

Verde Combo RM Thermoplastic Running Man Combo

Job/Location: _____

Contractor: _____ Prepared By: _____


Model Number: _____ Date: _____



EXTERNAL SPECIFICATIONS

The **VERDE COMBO** series is constructed from durable corrosion and flame resistant thermoplastic. The universal **VERDE** series comes standard with a mounting canopy, specified pictograms, one [1] backplate and all mounting hardware. The **VERDE** series comes standard finished in white. An external LED status indicator and test switch is standard. Enclosed lamp assemblies are fully adjustable and can be rotated and angled to provide exact aiming.

DIMENSIONS (MM, IN.)



Series	A	B	C	D	E
VE-RM	362mm	305mm	83mm	324mm	127mm
	14 ^{1/4"}	12"	3 ^{1/4"}	12 ^{3/4"}	5"

ORDERING INFORMATION

Series	Volts/Watts	Light Source	Face #	Pictogram	Mounting	Lamp	Options
VE-RM	12-25	L (LED)	1 (single)	OLR (Universal pictograms)	M (Universal mount)	See lamp selection	AT (Auto-test)
	12-50		*2 (double)	0 (No indicators)			SW (Special wording - specify)
			*U (Universal)	L (Left indicator)			WG (Wireguard)
				R (Right indicator)			BK (Black coloured housing)
				D (Down indicator)			BZ (Buzzer)
				U (Up indicator)			**TD (Time delay - specify 5, 10, 20 mins)
				UR (45° up right)			SW-OL (RM no indicator, left)
				DR (45° down right)			
				UL (45° up left)			
				DL (45° down left)			

NOTE: * Two pictograms or OLR must be ordered **AC voltage must be specified

EXAMPLE: VE-RM-12-50-L-1-UR-M-7WLED DESCRIPTION: Verde combo sign, 12V-50W, single face, universal mount, two 7 watt LED lamps, pictogram with up right indicator

INTERNAL SPECIFICATIONS

120/277/347VAC input is standard. **VERDE COMBO** is CSA 22.2 No. 141-15 Performance Certified.

MODEL RATING GUIDE

Model	Voltage	Wattage Rating 30 mins
VE-RM-12-25	12	25
VE-RM-12-50	12	50

LAMP SELECTION

12V	
MR16	20, 35, 50W
LED	2, 5, 7W

CHARGER SPECIFICATIONS

The **VERDE COMBO** series charger is a fully automatic current limited charger with solid state line latched low voltage disconnect protection. All components are temperature compensated. The charger also has brownout and short circuit protection. Charger status is determined via a dual diagnostic LED display that indicates AC ON and High Charge. A push button test switch allows maintenance personnel to quickly determine the status of the exit and lamp load on AC fail.

MODERN DESIGN

The low profile design of the **VERDE COMBO** exit provides a clean, attractive and affordable solution. The durable thermoplastic housing is corrosion and flame resistant. The modern and efficient design of the **VERDE** series allows for wall or ceiling mounting.

INSTALLATION

The **VERDE** is suitable for surface ceiling or wall mounting. Remotes cannot be connected to this combo. Suitable for indoor installations.

BEGHELLI AUTO-TEST (AT)

The Beghelli auto-test system automatically performs one 5 minute discharge test monthly and every 6 months it performs two 30 minute discharge tests, 24 hours apart. This tests both full battery capacity and recharge capability. The information is communicated simply and intuitively to maintenance personnel via a single multicolour LED. No need to memorize complex indicator protocols. No confusing array of multiple, same coloured LEDs that can be difficult to read from floor level.

ELECTRICAL SPECIFICATIONS

The **VERDE** series is configured with high-output LEDs to light the sign and supplied standard with 120/277/347VAC input. High-output LED technology provides energy savings, long life and even illumination levels. 120/277/347VAC input, maintenance free, Ni-MH batteries are protected by an electronic cut-off circuit that prevents over-discharge. External test switch and monitor LED are standard.

MECHANICAL SPECIFICATIONS

The **VERDE** series is constructed of durable corrosion and flame resistant thermoplastic. The **VERDE** series can be universally mounted single or double face. Canopy and mounting hardware are included.

BATTERY TECHNOLOGY

The **VERDE COMBO** series is designed with a maintenance free, Ni-MH batteries providing emergency lighting duration as specified per unit. Recharge time of the batteries is twenty-four [24] hours. The maximum battery operating temperature is +40°C and the minimum is +10°C.

UNIVERSAL PICTOGRAMS

The OLR (Universal) option includes: a pictogram with no directional indicators, a pictogram with a left facing directional indicator and a pictogram with a right facing directional indicator.



FACE OPTIONS

When ordering a single face, choose one pictogram option. When ordering a double face, choose 2 pictogram options. If the universal option is chosen, a set of 3 pictograms (OLR) will be provided.