


Mini Flood Light

30W | Colour Tunable | 120-277V



Ideal for landscaping, patio, and security lighting, signs, and building facades
Excellent replacement for quartz halogen fixtures

Die-Cast Aluminum Housing
with cooling fins for superior heat dissipation



Wattage Adjustable
(70-100%)

Built-in Photocell

56 LED Chips
for even illumination

0.5m Power Cord

High-Impact Polycarbonate Lens/Optics



Complete With Yoke Mount
Knuckle mount sold separately

Colour Tunable
3000K / 4000K / 5000K

Rugged Polyester Powder Coat Finish
(Bronze)

Optional Accessories:
Knuckle Mount (FLM-KNS)

Suggested Substitutions:
FLM-15W-40K-LV-YK
FLM-50W-3CCT-LV

TECHNICAL DATA



LIGHT SPECIFICATIONS


Lumens	4,141 lm
Efficacy	129.6 lm/W @ 4000K
CCT	3000K, 4000K, 5000K
CRI	70
L70 Life	50,000 hrs
Warranty	10-year

APPROVALS AND LISTINGS


cUL	E482965
DLC	PL3F7KBXG1NW

DIMENSIONS

Yoke Mount (Standard)



Knuckle Mount (Sold Separately)



ILLUMINANCE AT A DISTANCE

	Center Beam fc	Beam Width	
17.0ft	5.22 fc	31.3 ft	50.6 ft
34.0ft	1.31 fc	62.6 ft	101.2 ft
51.0ft	0.58 fc	93.9 ft	151.8 ft
68.0ft	0.33 fc	125.2 ft	202.4 ft
85.0ft	0.21 fc	156.5 ft	253.0 ft
102.0ft	0.15 fc	187.8 ft	303.6 ft

■ Vert. Spread: 85.3°
■ Horiz. Spread: 112.2°

ELECTRICAL

Wattage	30W (Adjustable 70-100%)
Voltage	120-277V
Power Factor	0.9
THD	15%
Operating Temp	-40 to 50°C


CONSTRUCTION

Housing	Aluminum Alloy
Finish	Bronze
IP Rating	IP65
Fixture Weight	1.1 kg
Carton Weight	11.2 kg
Carton Qty	8
Carton Dimensions	484 x 302 x 297 mm

ACCESSORIES (SOLD SEPARATELY)

Knuckle Mount	FLM-KNS
---------------	---------

ISOCANDELA

Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com