


DLC on Some
Linear Models


Date: _____ Fixture: _____

QTY: _____ Project: _____

Thinline 2.25

Wall Mount Indirect

Cast End Caps with Light Block

Multiple Lens and Customizations Available

Architectural luminaire. Wall mounting. Slim contemporary design. Aluminum extruded body. Continuous runs available. L90 > 70K Hours. Designed and manufactured in North America. 10 Year Warranty.

Performance

Color Temp	Lm/W
4000K	120 Lm/W
3500K	116 Lm/W
3000K	112 Lm/W

Ordering Options

MODEL	CONTINUOUS RUN	IND LUMENS	CRI	COLOR TEMP	VOLTAGE	LENS
DTL WM IND 2.25	CR _____ - Min 2' - Available in 6" increments - Unibody, up to 8'	I 250 I 500 I 750 I 1000 I _____ Custom Up to 1200	80 90	27K 2700K 3K 3000K 35K 3500K 4K 4000K 5K 5000K BIOS	U 120/277V H 347V	FR Frosted ASY Asymmetric BATWING

DTL WM IND 2.25						
-----------------	--	--	--	--	--	--

FINISH	MOUNTING	DRIVER	CONTROLS	CIRCUITS
GRY Grey WH White BLK Black CU Custom	WM Wall Mount 12EX 12" Extended Arm	DIMOFF 0-10 1% DIMOFF Driver LUTRON Lutron Ecosystem Driver SR Philips SR DALI .1% ELDO LED Driver * 347 only in 1 - 10 5%	N None DMX SNS Philips SNS 300 w/ BLD & Daylight CLM Encelium CLM LG LG Dongle BT Bluetooth Mesh EN Enlighted Integral	1 One circuit

				1
--	--	--	--	---

ACCESSORIES	WIRING
N None 10kV 10kV Surge Protection EMBAT 6W 90 Min BAT	N None (Will provide 5 Leads from mounting plate)

	N	
--	---	--

SAMPLE: DTL WM IND 2.25 - CR8 - I 500 - 80 - 4K - U - FR - WH - WM - DIMOFF - N - 1 - N - N

Available with BIOS® (please consult factory)

Specifications subject to change without notice.

Note: Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC qualified products list at www.designlights.org/qpl.

10YR
WARRANTY

LED

L90 > 70,000

Samsung 301 3 McAdam Binning


4000K 120 Lm/W

3500K 98%

3000K 96%


90 CRI 85%

Lens Options




2.25"

Indirect



2.25"


Asymmetric



2.25"

Batwing


Mounting



2.25"

Wall Mount Bracket

Secure light fixture
using #8-32 screws (2x)





12"

2.25"



12" Extended Arm

Measurements



2': 24.2", 3': 36.2", 4': 48.2", 5': 60.2", 6': 72.2", 7': 84.2", 8': 96.2"

Actual Length = NOMINAL +.2"




Mounting Location


Models	Mounting Lengths X
DTL 2	12"
DTL 3	18"
DTL 4	24"
DTL 5	30"
DTL 6	36"
DTL 7	42"
DTL 8	48"

Finishes


Standard Finishes



Delviro Grey
RAL 7046
Sandtex




Delviro White
RAL 9003
Sandtex




Delviro Black
RAL 9004
Sandtex


Custom Finishes




Delviro Orange
RAL 2009
Sandtex



Delviro Blue
RAL 5012
Sandtex



Delviro Yellow
RAL 1037
Sandtex



Delviro Green
RAL 6010
Sandtex

Additional Finishes Available - Please consult factory