

PR2110347 (Legacy*)



Ballast Type:	Electronic	Starting Method:	Rapid Start
Lamp Connection:	Series	Input Voltage:	347
Input Frequency:	50/60 Hz	Sound Rating:	A
Remote Mounting:	18 ft Maximum	Warranty:	One Year
End-of-Life Protection:	No	Max. Case Temperature:	90°C

ELECTRICAL SPECIFICATIONS

Lamp Type	# of Lamps	Rated Lamp Watts	Min. Start Temp. (°F/°C)	Input Current (Amps)	Input Power (Watts)	Ballast Factor	Max THD %	Power Factor	Max. L.C.C.F.	B.E.F
F96T12HO	2	110	-20 / -29	0.56	192	0.84	10	0.99	1.60	0.44
	1			0.32	110	0.88				0.80
F72T12HO	2	85		0.45	156	0.87	15			0.56
F48T12HO	2	60		0.34	117	0.89				0.76

REGULATORY COMPLIANCE


- Meets ANSI Standard C82.11
- Meets ANSI Standard C62.41
- Meets FCC Part 18 Class A for EMI & RFI (Non-Consumer Limits)

- No PCB's
- cULus Listed (Class P, Type 1 Outdoor, Type HL)
- RoHS Compliant




PHYSICAL CHARACTERISTICS

WIRING DIAGRAM



* Cap off each Yellow wire separately



LEAD LENGTH

Wire	in
Black	19
White	19
Blue	39
Red	39
Yellow	66

CASE DIMENSIONS

Overall (L)	11.61"	295.0 mm
Width (W)	2.40"	61.0 mm
Height (H)	1.57"	40.0 mm
Mounting (M)	11.26"	286.0 mm

ORDERING INFORMATION

Model #	Carton Weight	Carton Dimensions LxWxH	Carton Quantity	Skid Quantity
PR2110120M	32.6 lbs	14.2" x 12.6" x 5.8"	10	450