

PR232120M



Ballast Type:	Electronic	Starting Method:	Rapid Start
Lamp Connection:	Series	Input Voltage:	120 to 277
Input Frequency:	50/60 Hz	Sound Rating:	A
Remote Mounting:	18 ft Maximum	Warranty:	One Year
End-of-Life Protection:	No	Max. Case Temperature:	70°C

ELECTRICAL SPECIFICATIONS

Lamp Type	# of Lamps	Rated Lamp Watts	Min. Start Temp. (°F/°C)	Input Current (Amps) @120/277V	Input Power (Watts)	Ballast Factor	Max THD %	Power Factor	Max. L.C.C.F.	B.E.F	
F32T8	2	32	32 / 0	0.53 / 0.23	64	0.88	10	0.99	1.70	1.38	
	1			0.34 / 0.15	40	0.92	15			2.30	
F32T8/ES (30W)	2	30	60 / 16	0.49 / 0.21	59	0.88	10			1.49	
	1			0.29 / 0.13	35	0.93	15			2.66	
F32T8/ES (28W)	2	28		0.46 / 0.20	56	0.89	10			1.59	
	1			0.27 / 0.13	33	0.93	15			2.82	
F32T8/ES (25W)	2	25		0.43 / 0.19	52	0.90	10			1.73	
	1			0.26 / 0.12	31	0.93	15	0.98		3.00	
F25T8	2	25		32 / 0	0.43 / 0.19	52	0.90	10		0.99	1.73
	1				0.27 / 0.12	32	0.93	15		0.98	2.91
F17T8	2	17	0.31 / 0.13		38	0.93	15	0.99	2.45		
	1		0.21 / 0.09		25	0.94	15	0.98	3.76		

REGULATORY COMPLIANCE


- Meets ANSI Standard C82.11
- Meets ANSI Standard C62.41
- Meets FCC Part 18 Class A for EMI & RFI (Non-Consumer Limits)

- No PCB's
- cULus Listed (Class P, Type 1 Outdoor, Type HL)
- RoHS Compliant




PHYSICAL CHARACTERISTICS

WIRING DIAGRAM



*Cap off each Yellow wire separately



LEAD LENGTH

Wire	in
Black	18
White	18
Blue	31
Red	31
Yellow	46

CASE DIMENSIONS

Overall (L)	9.50"	241.0 mm
Width (W)	1.72"	43.8 mm
Height (H)	1.18"	30.0 mm
Mounting (M)	8.90"	226.0 mm

ORDERING INFORMATION

Model #	Carton Weight	Carton Dimensions LxWxH	Carton Quantity	Skid Quantity	Bulk Quantity
PR232120M	28.6 lbs	11.0" x 10.6" x 9.1"	20	960	1120