



|                      |                                       |
|----------------------|---------------------------------------|
| <b>Description</b>   | 12V 35W 38 Deg. Flood MR16 GU5.3 Base |
| <b>Ordering Code</b> | 15051                                 |
| <b>UNSPSC Code</b>   | 39101601                              |

## Specifications

|                                   |                    |
|-----------------------------------|--------------------|
| <b>Voltage Rating</b>             | 12                 |
| <b>Watts</b>                      | 35                 |
| <b>Amps</b>                       | 2.92               |
| <b>Base Type</b>                  | GU5.3              |
| <b>Bulb Type</b>                  | MR16               |
| <b>Filament</b>                   | C-8                |
| <b>MOL in/mm</b>                  | 1.81/46.0          |
| <b>MOD in/mm</b>                  | 2.00/50.8          |
| <b>Approx Initial Max Beam CP</b> | 900                |
| <b>CT deg K</b>                   | 2950               |
| <b>Beam Angle</b>                 | 38°                |
| <b>Beam Description</b>           | Flood              |
| <b>Rated Life</b>                 | 4,000              |
| <b>Common Code</b>                | Q35MR16/FL         |
| <b>Burning Position</b>           | Any                |
| <b>Special Desc</b>               | Dichroic Reflector |
| <b>Type Use</b>                   | Display 38         |

watch > like > follow



selection. solutions. simplicity. [eiko.com](http://eiko.com)

23220 W. 84<sup>th</sup> St, Shawnee, KS 66227 • (P) 1.800.852.2217 (F) 1.800.492.8975  
Canada: 81 King St, Barrie, ON L4N 6B5 • (P) 1.888.410.8151 (F) 1.888.705.1335