

A19 REPLACEMENT : E26 BASE

DESCRIPTION

LED A19 Replacement Lamps are a cost-effective, energy-efficient alternative to incandescent filament lamps.

FEATURES

- Direct replacement for 40 & 60W incandescent A lamps
- 240° beam angle is ideal for table lamps, wall sconces, and luminous globe fixtures
- 80% more efficient and 30x longer life than standard incandescent
- Smooth, clean outside housing
- Dimmable versions are compatible with a wide array of dimmers
- Comfortable diffused light
- Instant-On with no warm up, unlike CFLs
- Shatter resistant for reduced risk of injury and breakage
- Standard series 80+ CRI for enhanced color and lighting uniformity from lamp to lamp

WARRANTY

- 5 year limited warranty; see eiko.com for warranty details

APPLICATIONS

- Restaurants & Hospitality
- Retail
- Residential
- Accent/Display Lighting
- Healthcare



RoHS
Compliant

cUL US LISTED

PERFORMANCE	Power Consumption	6W	9W
	Lumens	450	800
	Efficacy (LPW)	75	89
	Beam	240°	
	CRI	80+	
	CCT	3000K, 4000K	
	Life (L70)	10,000 hours	
ELECTRICAL	Power Factor	≥0.9	
	THD	<20%	
	Input Voltage	120VAC	
CONSTRUCTION	Operating Temperature	-4°F to 104°F (-20°C to 40°C)	
	Base	E26	
LISTINGS	Certification(s)	cULus Listed	
	Material Usage	RoHS Compliant; no mercury or lead	
	Environment	Suitable for use in damp locations	

PERFORMANCE SUMMARY

Order Code	Item #	Lumens	Watts	CCT	CRI	Volts	Base	MOL	MOD	Dimming	Life/Hours
10106	LED6WA19/ADV/840-G8	450	6W	4000K	80+	120V	E26	4.21"	2.36"	Non-Dimmable	10,000
10107	LED9WA19/ADV/830-G8	800	9W	3000K	80+	120V	E26	4.21"	2.36"	Non-Dimmable	10,000
10282	LED9WA19/ADV/830-G9	800	9W	3000K	80+	120V	E26	4.21"	2.36"	Non-Dimmable	10,000
10281	LED9WA19/ADV/830-DIM-G9	800	9W	3000K	80+	120V	E26	4.21"	2.36"	Dimmable	10,000

NOTE: Use order code when ordering.

DIMENSIONS



Wattage	MOL	MOD
6W	4.21"/108mm	2.36"/60mm
9W	4.21"/108mm	2.36"/60mm