

A19 REPLACEMENT : E26 & GU24 BASE

DESCRIPTION

LED A19 Replacement Lamps directly replace incandescent A19 lamps at a fraction of the energy cost.

FEATURES

- Direct replacement for 40, 60, 75, and 100W incandescent A-lamps
- 300° Omni beam angle is ideal for table lamps, wall sconces, and luminous globe fixtures
- 80% more efficient and 30x longer life than standard incandescent
- Compatible with a wide array of dimmers
- Shatter-resistant plastic housing for reduced risk of injury and breakage

WARRANTY

- 5 year limited warranty; see eiko.com for warranty details

APPLICATIONS

- Restaurants & Hospitality
- Retail
- Residential
- Accent/Display Lighting
- Healthcare



A19 E26



A19 GU24



PERFORMANCE	Power Consumption	6W	9W	11W	15W
	Lumens	480	800	1,100	1,600
	Efficacy (LPW)	80	89	100	107
	CRI	80+			
	Beam	300°			
	CCT	2700K, 3000K, 4000K			
	Life (L70)	25,000 hours			
ELECTRICAL	Power Factor				
	Input Voltage	120V			
CONSTRUCTION	Operating Temperature	-4°F to 104°F (-20°C to 40°C)			
	Base	E26, GU24			
LISTINGS	Certification(s)	ENERGY STAR® Rated; cULus Classified; LM70			
	Material Usage	RoHS Compliant; no mercury or lead			
	Environment	Enclosed fixture rated; Suitable for dry or damp locations			

PERFORMANCE SUMMARY

MEDIUM BASE (E26):

Order Code	Item #	Lumens	Watts	LPW	CCT	CRI	Volts	Life/Hours	Replaces Incan.	ES
10274	LED6WA19/OMN/827-DIM-G9	480	6W	80	2700K	80+	120V	25,000	40W	
10276	LED6WA19/OMN/830-DIM-G9	480	6W	80	3000K	80+	120V	25,000	40W	★
10277	LED6WA19/OMN/840-DIM-G9	480	6W	80	4000K	80+	120V	25,000	40W	★
10283	LED9WA19/OMN/827-DIM-G9	800	9W	89	2700K	80+	120V	25,000	60W	★
10285	LED9WA19/OMN/830-DIM-G9	800	9W	89	3000K	80+	120V	25,000	60W	★
10287	LED9WA19/OMN/840-DIM-G9	800	9W	89	4000K	80+	120V	25,000	60W	★
10289	LED9WA19/OMN/850-DIM-G9	800	9W	89	5000K	80+	120V	25,000	60W	★
10269	LED15WA19/OMN/827-DIM-G9	1,600	15W	107	2700K	80+	120V	25,000	100W	
10270	LED15WA19/OMN/830-DIM-G9	1,600	15W	107	3000K	80+	120V	25,000	100W	
10271	LED15WA19/OMN/840-DIM-G9	1,600	15W	107	4000K	80+	120V	25,000	100W	
10273	LED15WA19/OMN/850-DIM-G9	1,600	15W	107	5000K	80+	120V	25,000	100W	

GU24 BASE:

Order Code	Item #	Lumens	Watts	LPW	CCT	CRI	Volts	Life/Hours	Replaces Incan.	ES
10284	LED9WA19/OMN/827-GU24-DIM-G9	800	9W	89	2700K	80+	120V	25,000	60W	★
10286	LED9WA19/OMN/830-GU24-DIM-G9	800	9W	89	3000K	80+	120V	25,000	60W	★
10288	LED9WA19/OMN/840-GU24-DIM-G9	800	9W	89	4000K	80+	120V	25,000	60W	★
10266	LED11WA19/OMN/827-GU24-DIM-G9	1,100	11W	100	2700K	80+	120V	25,000	75W	
10267	LED11WA19/OMN/830-GU24-DIM-G9	1,100	11W	100	3000K	80+	120V	25,000	75W	
10268	LED11WA19/OMN/840-GU24-DIM-G9	1,100	11W	100	3000K	80+	120V	25,000	75W	

DIMENSIONS



Wattage/Base	MOL	MOD
6-9W/E26	4.21"/106.9mm	2.36"/59.9mm
15W/E26	4.61"/117.1mm	2.36"/59.9mm
9-11W/GU24	4.21"/106.9mm	2.36"/59.9mm