

ELX-645

Chicago Approved Recessed Mount LED
Edge-Lit Exit Signs

Architectural Exit Sign

Catalog Number:

Project Name:

Note:

Type:



ILLUMINATION

- Ultra-bright, energy efficient, long-lasting white LEDs provide uniform illumination.
- UV stabilized, silk screened acrylic panels provide consistent, uniform illumination.
- Single or double face configurations.

ELECTRICAL

- Dual 120V/277V.
- Charge rate/power "ON" LED indicator light and push to test switch for mandated code compliance testing.
- 4.8V Long-life, maintenance-free, rechargeable NiCad battery (EM models only).
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 120-minute emergency illumination.
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

- Compatible with drywall or drop-through ceiling mount installations.
- Wall mount capability optional.

HOUSING

- Premium-grade, extruded aluminum housing.
- Trim assembly is easily detachable, providing accessibility for service or maintenance.

WARRANTY/LISTING

- Five year warranty on all electronics and housing. Battery prorated for five years.
- UL listed for damp locations (0°-50°C/32°F-122°F standard).
- Meets UL924, NFPA101 Life Safety Code, NEC, OSHA, Local and State Codes.
- Meets city of Chicago requirements.



ELX-645 - ITEM SELECTOR: (Please check the boxes below for the option desired)

LETTER COLOR	HOUSING COLOR	NO. OF FACE	BATTERY	EXIT (SIGNAGE)		STAIRS (SIGNAGE)	
☐ R - Red on white	☐ AL - Aluminum ☐ W - White	☐ 1 - Face ☐ 2 - Face	☐ AC - AC only ☐ EM - Emergency Back-up	☐ ENA - Exit No Arrow		☐ SNA - Stairs No Arrow	
				☐ EDA - Exit Double Arrow		☐ SDA - Stairs Double Arrow	
				☐ ERA ¹ - Exit Right Arrow		☐ SRA ¹ - Stairs Right Arrow	
				☐ ELA ¹ - Exit Left Arrow		☐ SLA ¹ - Stairs Left Arrow	
				☐ ELRA ² - Exit Left/Right Arrow		☐ SLRA ² - Stairs Left/Right Arrow	
				MOUNTING OPTION			
			☐ WM - Wall Mount				

Notes:

¹. Available in single face configuration only • ². Available in double face configuration only

SPECIFIED:

ELX-645

LETTER COLOR

HOUSING COLOR

NO. OF FACE

BATTERY OPTION

MOUNTING

DIRECTIONAL ARROWS