

ELX-713

LED Exit/Emergency Light Combo W/ Battery Back-Up & Remote Capable

Exit/Emergency Light Combo


Catalog Number:

Project Name:

Type:

Note:

MAXILUME
ARCHITECTURAL LIGHTING



FEATURES

This product is an ideal when both an exit sign and an emergency light are required. Its design makes it suitable for use above doors or in other tight spaces. Full-range control of direction is made possible by the swivel-and-point design of the LED head. The operation of the product can easily be monitored and controlled with the use of a conveniently located test switch that indicates charge and diagnostic state. LED and PC circuitry have a rating of about 25 years without a drop in illumination.

BODY

- The thermoplastic housing of the product makes it corrosion-proof and scratch-and impact-resistant.
- UV-stabilization prevents discoloration of the product.
- Every fixture includes a canopy, extra faceplate, and replaceable chevron directional indicator knockouts for control of direction.
- Compartment shaped by injection.

FACE

- Single or dual configuration. Solid face included if single face appearance is preferred
- 6" high text with color diffusion
- Knockout directional chevrons

MOUNTING

- Unique "snap-together" universal mounting design permits top, back and side mounting. Necessary hardware and canopy are provided electrical

ELECTRICAL

- Minimum 90 minutes of illumination
- 120V or 277V Dual Input
- Normally uses 3.8 watts of power, 15 watts in emergency use
- When battery is functioning, LED lights flash
- Emergency lighting by two adjustable, glare-free light heads 1W (8 LED's x 0.125) per head

BATTERY

- 6V 4.5 amp, sealed-lead acid battery
- Minimum 120 minutes of illumination
- Solid-state internal circuitry for charging

OPTIONS


- RC: Remote capacity of up to 3.0 watts

TESTING

- Test Button
- Indicator light shows high charge and readiness for operation
- Safeguards against surges and short circuits

LISTED

- UL 924, NFPA, NEC, State & Municipal
- Damp location approved



ELX-713 - ITEM SELECTOR: (Please check the boxes below for the option desired)

LETTER COLOR	HOUSING COLOR
☐ G - Green	☐ W - White
☐ R - Red	☐ B - Black

Specified:

ELX-713 _____ - _____
LETTER COLOR HOUSING COLOR



MAXILUME
ARCHITECTURAL LIGHTING

A division of
Elite Lighting

Submittal form is available @ www.maxilume.com
Tel: 323-888-1973 • Fax: 323-888-1977

Specifications and Dimensions
subject to change without notice.

REV: MAXILUME-SPEC-03-10-2011