

T5 10.5W HO 2FT. DIR

TITANIUM LED SERIES



PRO




10.5W REPLACES



24W
Fluo.

60% Energy Savings

- Compatible with Instant Start & Programmed Start ballasts
- Easy to install - Plug & Play Direct
- Exceptional efficacy 152 LPW
- Suitable for use in totally enclosed fixtures
- Powerful light output 1600 lumens
- Dimmable



LM 79

LM 80

TM 21

IES



HIGH LUMEN EFFICIENCY - SUPERIOR PERFORMANCE



T5 10.5W HO 2FT. DIR

TITANIUM LED SERIES



SPECIFICATIONS**

Product Model	98165 10.5T5HO/2F/830/DIR	98166 10.5T5HO/2F/835/DIR	98167 10.5T5HO/2F/840/DIR
Type	T5	T5	T5
Base	Mini Bi-Pin G5	Mini Bi-Pin G5	Mini Bi-Pin G5
Power (W)	10.5	10.5	10.5
System Power (W)	14	14	14
Voltage - Frequency	120-277V 50-60Hz	120-277V 50-60Hz	120-277V 50-60Hz
Color Temp. (ANSI)	Warm White 3000K	Neutral White 3500K	Cool White 4000K
CRI (Ra)	82	82	82
Typical lumens (lm)	1500	1500	1600
Efficacy (LPW)	143	143	152
System Efficacy	107	107	114
Light Emitting Area	270°	270°	270°
Beam Angle	120°	120°	120°
Dimmable	Yes	Yes	Yes
Power Factor	0.9	0.9	0.9
THD	<20%	<20%	<20%
Rated Lifetime - L70 (hrs.)	50,000	50,000	50,000
Temperature Rating	-4°F/-20°C - 95°F/35°C	-4°F/-20°C - 95°F/35°C	-4°F/-20°C - 95°F/35°C
MIN. Compartment Dimensions	24-13/16"(L)x13-3/16"(W)x3-1/8"(H)	24-13/16"(L)x13-3/16"(W)x3-1/8"(H)	24-13/16"(L)x13-3/16"(W)x3-1/8"(H)
Dia. x MOL	0.67"x22.13"	0.67"x22.13"	0.67"x22.13"
Weight (lb. / g)	0.18lb.	0.18lb.	0.18lb.

PROGRAM START BALLAST PERFORMANCE

Bare Lamp (W)	System (W)	3000K Lumens	3500K Lumens	4000K Lumens
10.5	14	1500	1500	1600

Testing Method: Above system power is half the total system power of a 2-tube installation using an electronic ballast. Power and lumen output will vary based on ballast and fixture type. Above data is indicative only.

* Suitable for use in totally enclosed fixtures

** Specification data is preliminary and may be subject to change

*** Suitable for damp locations. Not for use where directly exposed to the weather or water

**** This product conforms to the NSF/ANSI 2 standard and may be used in Splash Zones of Food Equipment. This product does not contain glass or any other hazardous materials.

Ref.#: DS256-T5-10.5W-HO-2FT-260218