

Kellems® Wire Management Products

PG and Metric Threaded Deluxe Cord Grips

Aluminum Fittings, Stainless Steel Mesh, Liquidtight, for Insulated Cables

**WARNING!**

It is important that you read all breaking strength, safety and technical data relating to this product on pages T-71 through T-76.



Straight PG Male



Straight Metric Male

Straight PG* Male Thread

Cord Diameter Range		Hub Size	Catalog Numbers
Inches	(cm)		
.500"-.625"	(1.27-1.59)	PG16	074PG16010
.500"-.625"	(1.27-1.59)	PG21	074PG21010
.625"-.750"	(1.59-1.90)	PG21	074PG211247
.750"-.875"	(1.90-2.22)	PG21	074PG211248
.625"-.750"	(1.59-1.90)	PG29	074PG29021
.750"-.875"	(1.90-2.22)	PG29	074PG29023
.875"-1.000"	(2.22-2.54)	PG29	074PG29025
1.125"-1.250"	(2.86-3.17)	PG29	074PG291028**
1.125"-1.250"	(2.86-3.17)	PG36	074PG36028**

* Panzergewinde

**Cable jacket may have to be stripped to pass through connector body.

Straight Metric Male Thread

Cord Diameter Range		Form Size	Catalog Numbers
Inches	(cm)		
.500"-.625"	(1.27-1.59)	F2	074M20010
.625"-.750"	(1.59-1.90)	F3	074M251247
.750"-.875"	(1.90-2.22)	F3	074M251248
.625"-.750"	(1.59-1.90)	F2	074M25017
.750"-.875"	(1.90-2.22)	F4	074M32021
.875"-1.000"	(2.22-2.54)	F4	074M32023
1.125"-1.250"	(2.86-3.17)	F4	074M32025
1.125"-1.250"	(2.86-3.17)	F5	074M321028
1.125"-1.250"	(2.86-3.17)	F5	074M321250

Specifications

Material	Temperature Range
Aluminum	-30°F to +240°F (-34°C to +115°C).
Stainless Steel (Gotcha Rings)	-30°F to +240°F (-34°C to +115°C).
Neoprene (Bushings)	-30°F to +240°F (-34°C to +115°C).
Hazardous Locations	Suitable for use in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 N.E.C. Reference 501.10(b)(2), 502.10(a)(2), 502.10(b)(2), 503.10(a)(2) and 503.10(b).

Approvals

Cord Connectors	UL Listed in accordance with Standard 514B.
Deluxe Cord Grips	UL Control numbers 898D and 899D.

Wet Locations

Suitable for use in wet locations when used with a listed nylon washer between box and fitting.

When used with a metal clad o-ring, product has UL 4X environmental rating.

Note: *Cable jacket may have to be stripped to pass through connector body. Kellems® Deluxe Cord Grips are suitable for use in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 of the National Electric Code Sections 501.10(b)(2), 502.10(a)(2), 502.10(b)(2), 503.10(a)(2) and 503.10(b).