

Signal-Quick™ Sight Glass Mounts




Sight Glass Mounts

Quickly attach tubular proximity sensors to glass and plastic indicator tubes for level detection.

- Rapid “out of tank” adjustments.
- Simple sensor change-out/replacement.
- For 9.5mm (3/8") to 44mm (1 3/4") tubes.
- Stainless steel and Delrin® Construction.

Specifications

Material:	Delrin® (body), stainless steel (hardware)
Pipe Range:	3/8" - 1 3/4"



Conduit Adapter

Catalog No.	Style	A	B	C	D	E	F	G
SGM12D	12mm	0.48 (12.2)	0.77 (19.6)	1.50 (38.1)	1.16 (29.5)	0.51 (13)	0.42 (10.5)	0.37-.81 (9.40-20.6)
SGM18D	18mm	0.71 (19.6)	1.0 (25.4)	1.75 (44.5)	1.50 (38.1)	0.63 (15.9)	0.46 (11.7)	0.63-1.12 (16.0-28.4)
SGM30D	30mm	1.19 (30.1)	1.45 (36.8)	2.75 (69.9)	2.67 (67.8)	1.25 (31.8)	0.75 (19.1)	1.0-1.7" (25.4-44.5)

Signal-Quick™ Conduit Adapters



Conduit Adapters

Seal your sensor and the cable in conduit for harsh environments. One end is threaded for 1/2" conduit and the other for standard 12, 18 or 30mm sensors.

- Round steel or Hex aluminum styles.
- Fully threaded to accommodate all sensors.

Specifications

Material:	Zinc-plated Steel (round) Aluminum (hex)
-----------	---

Round
body



Hex
body

Conduit Adapter

Catalog No.	Sensor Style	Description	A	B	C
CAR12	M12	Round Conduit Adapter	M12 x 1	0.69 (17.5)	1.97 (50)
CAH12	M12	Hex Conduit Adapter	M12 x 1	0.99 (25.1)	1.97 (50)
CAR18	M18	Round Conduit Adapter	M18 x 1	0.84 (21.3)	2.18 (55.4)
CAH18	M18	Hex Conduit Adapter	M18 x 1	0.99 (25.1)	2.18 (55.4)
CAR30	M30	Round Conduit Adapter	M30 x 1.5	1.31 (33.3)	2.68 (68.1)
CAH30	M30	Hex Conduit Adapter	M30 x 1.5	1.37 (34.9)	2.68 (68.1)

