

Deluxe Cord Grips

Nylon Fittings, Non-metallic Mesh, Liquidtight, for Insulated Cables and
Stainless Steel Fittings, Stainless Steel Mesh, Liquidtight, for Insulated Cables

WARNING!

It is important that you read all breaking strength, safety and technical data relating to this product on pages T-71 through T-76.

Nylon Fittings Non-metallic Mesh, Liquidtight for Insulated Cables Straight Male Thread

Grip Diameter Range Inches	(cm)	Thread Size N.P.T. (Inches)	Form Size	Catalog Numbers
.187"-.250"	(.47-.63)	3/8	F1	CG304NM
.250"-.312"	(.63-.79)			CG305NM
.312"-.375"	(.79-.95)			CG306NM
.187"-.250"	(.47-.63)	1/2	F2	CG404NM
.250"-.375"	(.63-.95)			CG406NM
.375"-.500"	(.95-1.27)			CG408NM
.375"-.500"	(.95-1.27)	3/4	F3	CG608NM
.500"-.625"	(1.27-1.59)			CG610NM
.625"-.750"	(1.59-1.90)			CG612NM
.500"-.625"	(1.27-1.59)	1	F4	CG810NM
.625"-.750"	(1.59-1.90)			CG812NM
.750"-.875"	(1.90-2.22)			CG814NM
.875"-1.000"	(2.22-2.54)			CG816NM

90° Male Thread

Grip Diameter Range Inches	(cm)	Thread Size N.P.T. (Inches)	Form Size	Catalog Numbers
.250"-.375"	(.63-.95)	1/2	F2	CG40690NM
.375"-.500"	(.95-1.27)			CG40890NM
.375"-.500"	(.95-1.27)	3/4	F3	CG60890NM
.500"-.625"	(1.27-1.59)			CG61090NM
.625"-.750"	(1.59-1.90)			CG61290NM*
.625"-.750"	(1.59-1.90)	1	F4	CG81290NM
.750"-.875"	(1.90-2.22)			CG81490NM

* Cable jacket may have to be stripped to pass through connector body.

Note: Non-metallic locknuts are available upon request. Refer to page T-89.

Stainless Steel Fittings, Stainless Steel Mesh, Liquidtight for Insulated Cables Straight Male Thread

Grip Diameter Range Inches	(cm)	Thread Size N.P.T. (Inches)	Form Size	Catalog Numbers
.187"-.250"	(.47-.63)	1/2	F2	CG404SST
.250"-.375"	(.63-.95)			CG406SST
.375"-.500"	(.95-1.27)			CG408SST
.500"-.625"	(1.27-1.59)			CG410SST
.375"-.500"	(.95-1.27)	3/4	F2	CG608SST
.500"-.625"	(1.27-1.59)			CG610SST
.625"-.750"	(1.59-1.90)	3/4	F3	CG612SST
.750"-.875"	(1.90-2.22)			CG614SST
.500"-.625"	(1.27-1.59)	1	F4	CG810SST
.625"-.750"	(1.59-1.90)			CG812SST
.750"-.875"	(1.90-2.22)			CG814SST
.875"-1.000"	(2.22-2.54)			CG816SST



Straight Male



90° Male



Straight Male

Note: *Cable jacket may have to be stripped to pass through connector body. Kellems® Deluxe Cord Grips are suitable for use in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 of the National Electric Code Sections 501.10(b)(2), 502.10(a)(2), 502.10(b)(2), 503.10(a)(2) and 503.10(b).