

Marine Products Boatyard Accessory Items

Marine Grade Outlet Box Hoods



**IMPROVED
DESIGN**



RW57500



RW57600



RW57950



HBL6085



HBL10CM22S

IP66

SUITABILITY Enclosures only.

Marine Grade Outlet Box Hoods

Description	Color	Mounting	Catalog Numbers
Standard Cover, 1-Gang, For Duplex, GFCI, Toggle and Single Receptacles, Diameter 1.34, 1.40, 1.60, 1.72, 2.03 and 2.15 inch	Gray	Horizontal or Vertical	RW57500
Deep Cover, 1-Gang, For Duplex, GFCI, Toggle and Single Receptacles, Diameter 1.34, 1.40, 1.60, 1.72, 2.03 and 2.15 inch	Gray	Horizontal or Vertical	RW57600
Deep Cover, 2-Gang, For Single Receptacles, Diameter 1.34, 1.40, 1.60, 1.72, 2.03 and 2.15 inch	Gray	Vertical	RW57950



Nylon Watertight Strain Relief Cord Connectors

These Hubbell nylon cord connectors provide strain relief and a watertight seal where cable enters a piece of equipment, panel, or box. A patented GOTCHA® ring, with a split and hinge design, allows for better adjustment to the cord as the connector nut is tightened, providing superior cord gripping compared to other types. A soft neoprene bushing compresses to keep liquids out and allows the nut to be easily tightened.

Description	Catalog Numbers
A gray male PVC adapter with 3/4 in. N.P.T. pipe thread for adapting PVC conduit to FS and FD boxes with 3/4 in. N.P.T. hub (HBL6080, HBL6080OS, HBL60CM83). Not UL Listed.	HBL6085
Straight nylon cord connector, 1/2 in. N.P.T. hub size, diameter range .25-.38 in. (6.4-9.5).	HBL10CM22S
Straight nylon cord connector, 1/2 in. N.P.T. hub size, diameter range .38-.50 in. (9.5-12.7).	HBL10CM23S
Straight nylon cord connector, 3/4 in. N.P.T. hub size, diameter range .38-.50 in. (9.5-12.7).	HBL10CM35S
Straight nylon cord connector, 3/4 in. N.P.T. hub size, diameter range .50-.63 in. (12.7-15.9).	HBL10CM36S
Straight nylon cord connector, 3/4 in. N.P.T. hub size, diameter range .63-.75 in. (15.9-19.1).	HBL10CM37S
Straight nylon cord connector, 1.0 in. N.P.T. hub size, diameter range .63-.75 in. (15.9-19.1).	HBL10CM41S