



Marine Products Adapter Selection Guide

Boat/Cable Set Side

Connector Body (Female End)

Molded Straight Adapters Catalog Number

Power Center/Dock Side

Plug (Male End)

15A 125V, 2P 3W Straight		HBL105GF*		30A 125V, 2P 3W Twist-Lock®
30A 125V, 2P 3W Twist-Lock®		HBL61CM22 HBL61CM22W		15A 125V, 2P 3W Straight Blade (lock type)
30A 125V, 2P 3W Twist-Lock		HBL61CM25		20A 125V, 2P 3W Twist-Lock
50A 125V, 2P 3W Twist-Lock		HBL61CM54		15A 125V, 2P 3W Straight Blade
30A 125V, 2P 3W Twist-Lock		HBL61CM55		50A 125V, 2P 3W Twist-Lock
50A 125V, 2P 3W Twist-Lock		HBL61CM56		30A 125V, 2P 3W Twist-Lock
50A 125/250V, 3P 4W Twist-Lock		HBL61CM59		50A 125/250V, 3P 4W Crow Foot
30A 125V, 2P 3W Twist-Lock		HBL61CM71		50A 125/250V, 3P 4W Twist-Lock
50A 125V, 2P 3W Twist-Lock		HBL61CM72		50A 125/250V, 3P 4W Twist-Lock
100A 125/250V, 3P 4W Pin/Sleeve		HBL61CM100		50A 125/250V, 3P 4W Twist-Lock

Molded “Y” Adapters

(2) 30A 125V, 2P 3W Twist-Lock			HBL64CM54		50A 125/250V, 3P 4W Twist-Lock
(2) 50A 125V, 2P 3W Twist-Lock			HBL64CM55		50A 125/250V, 3P 4W Twist-Lock
(2) 30A 125V, 2P 3W Twist-Lock			HBL64CM56		30A 125V, 2P 3W Twist-Lock
(2) 30A 125V, 2P 3W Twist-Lock			HBL64CM57		50A 125V, 2P 3W Twist-Lock
(2) 30A 125V, 2P 3W Twist-Lock			HBL64CM59		50A 125/250V, 3P 4W Crow Foot

One Piece Adapters

30A 125V, 2P 3W Twist-Lock		HBL31CM28		15A 125V, 2P 3W Straight Blade
15 or 20A 125V, 2P 3W Straight Blade		HBL31CM29		30A 125V, 2P 3W Twist-Lock
20A 125V, 2P 3W Twist-Lock		HBL21CM28		15A 125V, 2P 3W Straight Blade
15 or 20A 125V, 2P 3W Straight Blade		HBL21CM29		20A 125V, 2P 3W Twist-Lock

Note: See following two pages for photographs and descriptions.

* Provides GFCI Protection



Marine Products

Molded Straight Adapters

IP65
SUITABILITY



HBL21CM28



HBL21CM29



HBL31CM28



HBL31CM29

Molded Straight Adapters

Description	Catalog Numbers
Permits use of 20A 125V Twist-Lock® locking type plug with 15 or 20A 125V straight blade receptacle. IP20 SUITABILITY.	HBL21CM28†
Permits use of 15A or 20A 125V straight blade plug with 20A 125V Twist-Lock locking type receptacle. IP20 SUITABILITY.	HBL21CM29†
Permits use of 30A 125V Twist-Lock locking type plug with 15 or 20A 125V straight blade receptacle. IP20 SUITABILITY.	HBL31CM28
Permits use of 15A or 20A 125V straight blade plug with 30A 125V Twist-Lock locking type receptacle. IP20 SUITABILITY.	HBL31CM29
Permits use of 30A 125V cable set, HBL61CM08, with 15 or 20A 125V straight blade receptacle. Anchor locking screw on plug when screwed down resists pullout of the cable set.	HBL61CM22
Same as HBL61CM22, except white.	HBL61CM22W
Permits use of 30A 125V cable set, HBL61CM08, with 20A 125V Twist-Lock receptacle, HBL23CM10.	HBL61CM25
Permits use of 50A 125V cable set, HBL61CM53, with 15 or 20A 125V straight blade receptacle.	HBL61CM54
Permits use of 30A 125V cable set, HBL61CM08, with 50A 125V Twist-Lock receptacle, HBL63CM70.	HBL61CM55
Permits use of 50A 125V cable set, HBL61CM53, with 30A 125V Twist-Lock receptacle, HBL26CM10.	HBL61CM56
Permits use of 50A 125/250V Twist-Lock locking type cable set, HBL61CM52, with 50A 125/250V crow foot straight blade receptacle HBL7962.	HBL61CM59
Permits use of 30A 125V cable set, HBL61CM08, with 50A 125/250V Twist-Lock receptacle, HBL63CM69.	HBL61CM71 ▲
Permits use of 50A 125V cable set, HBL61CM53, with 50A 125/250V Twist-Lock receptacle, HBL63CM69.	HBL61CM72 ▲
Permits use of 15A 125V 3 wire straight blade plug with 15 or 20A 125V 2 wire straight blade receptacle.	HBL5273L †
Permits a 100 amp 125/250 volt cable set to plug into a single 50 amp 125/250 volt outlet.	HBL61CM100
Permits use of 15A straight blade plug with 30A 125V Twist-Lock receptacle; with GFCI protection.	HBL105GF

Notes: † UL listed.

Adapters do not provide overcurrent protection.

Adapters do not provide GFCI protection except HBL105GF.

▲ The male plug end (50A 125/250V) has a blade removed and the blade slot filled with epoxy. Omitting the blade ensures achieving 125V safely.



HBL61CM22



HBL61CM25



HBL61CM54



HBL61CM55



HBL61CM59



HBL61CM56



HBL61CM100



HBL105GF



HBL61CM71 ▲



HBL61CM72 ▲