

Straight Blade Devices

2 Pole, 3 Wire Grounding

15 and 20 Ampere, 125 Volts

INSULGRIP® Heavy Duty Plugs



IP20
SUITABILITY



NEMA 5-15P
15A 125V
UL CSA
0.5 HP



NEMA 5-20P
20A 125V
UL CSA
1 HP

Insulgrip Plugs

Description	Cord Dia.	Catalog Numbers	
Black and white nylon.	.230"-.720" (5.8-18.3)	HBL5266C™	HBL5366C™
Corrosion resistant yellow nylon.	.230"-.720" (5.8-18.3)	HBL52CM66C	HBL53CM66C
8-position angle plug, black and white nylon.	.325"-.655" (8.3-16.6)	HBL5266CA	HBL5366CA
8-position angle plug, transparent enclosure.	.325"-.655" (8.3-16.6)	HBL5266CAT	—
Anchor lock, black and white nylon. ⁽¹⁾	.230"-.720" (5.8-18.3)	HBL5280C	—
Anchor lock, corrosion resistant yellow nylon. ⁽¹⁾	.230"-.720" (5.8-18.3)	HBL52CM80C	—
Finger grip, black neoprene, combination screws. CSA only.	.312"-.468" (7.9-11.9)	HBL5921	—
Fusible, black vinyl housing, slotted screws. CSA only.	.296"-.625" (7.5-15.9)	HBL5299	—

Insulgrip Hospital Grade Plugs

Description	Cord Dia.	Catalog Numbers	
Black and white nylon.	.230"-.720" (5.8-18.3)	HBL8215C™	HBL8315C
Transparent housing.	.230"-.720" (5.8-18.3)	HBL8215CT	HBL8315CT
8-position angle plug, transparent housing.	.250"-.655" (6.4-16.6)	HBL8215CAT	HBL8315CAT

Accessories

Seal-Tite® triple seal, black elastomer cover for Insulgrip® plugs when used in a cord set, and connector bodies when used with flanged inlets.	HBL6017*
Same as above except yellow.	HBL60CM17*
PLUGOUT® Lockout device for Hubbell plugs and others.	HLD

Notes: See page A-39 for accessories. See page A-42 for technical information.

⁽¹⁾UL component listed only. Not for general use applications.

*IP55 when installed and used properly with mating components.

