

IEC Pin and Sleeve

Fused Circuit-Lock® Ordering Information

30 and 60 Ampere – North American Ratings

IP66
SUITABILITY

ACFSNO



MICPK30



HBLRFT2

Amps	Poles & Wires	Configuration Recep./ Conn.	Plug/ Inlet	Voltage	Mechanical Interlock	Mating Plug
30	3P 4W			120/240	HBL430MIF12W	HBL430P12W
	3P 4W			3Ø 240	HBL430MIF9W	HBL430P9W
	3P 4W			3Ø 480	HBL430MIF7W	HBL430P7W
	3P 4W			3Ø 600	HBL430MIF5W	HBL430P5W
	4P 5W			3Ø Y 277/480	HBL530MIF7W	HBL530P7W
	4P 5W			3Ø Y 347/600	HBL530MIF5W	HBL530P5W
60	3P 4W			120/240	HBL460MIF12W	HBL460P12W
	3P 4W			3Ø 240	HBL460MIF9W	HBL460P9W
	3P 4W			3Ø 480	HBL460MIF7W	HBL460P7W
	3P 4W			3Ø 600	HBL460MIF5W	HBL460P5W
	4P 5W			3Ø Y 120/208	HBL560MIF9W	HBL560P9W

Note: 30A – 1.0 inch N.P.T. hub supplied; 60A – 1¼ inch hub supplied.

Auxiliary Contacts**Description**

Auxiliary contact, normally open, A600 pilot duty.

Auxiliary contact, normally closed, A600 pilot duty.

Catalog Number

ACFSNO

ACFSNC

Watertight Closure Plug Kits**Description**

For 30A Circuit-Lock Unfused and Fused Pin and Sleeve mechanical interlocks.

For 60A and 100A Circuit-Lock Unfused and Fused Pin and Sleeve mechanical interlocks.

Catalog Number

MICPK30

MICPK60

Replacement Mounting Feet**Description**

Replacement mounting feet and screws for 30A and 60A fused mechanical interlocks.

Catalog Number

HBLRFT2*

*Package of 10 feet and 10 screws.

Dimensions