


Straight Blade Devices


2 Pole, 3 Wire Grounding

15 and 20 Ampere, 125 Volts


INSULGRIP® Connector Bodies



HBL5269C



HBL8219C



HBL6334CCN



NEW

IP20
SUITABILITY



Insulgrip Connector Bodies – Phillips/Slotted Screws

Description	Cord Dia.	Catalog Numbers	
Black and white nylon.	.230-.720" (5.8-18.3)	HBL5269C™	HBL5369C™
Black and white nylon.	.230-.720" (5.8-18.3)	HBL5269CCN™*	–
Corrosion resistant yellow nylon.	.230-.720" (5.8-18.3)	52CM69C	53CM69C
Steel armored, brown phenolic, slotted screws.	.296-.625" (7.5-15.9)	5269	–

Insulgrip Hospital Grade, Connector Bodies – Phillips/Slotted Screws

Description	Cord Dia.	Catalog Numbers	
Black and white nylon.	.230-.720" (5.8-18.3)	HBL8219C™	HBL8319C
Black and white nylon.	.230-.720" (5.8-18.3)	HBL8219CCN™*	–
Transparent enclosure.	.230-.720" (5.8-18.3)	HBL8219CT	HBL8319CT
Transparent enclosure.	.230-.720" (5.8-18.3)	HBL8219CTCN*	–

*Note: Catalog numbers listed above with suffix CN have combination
Robertson/slotted head terminal and assembly screws.



IP20
SUITABILITY



Insulgrip Connector Bodies – Robertson/Slotted Screws

Description	Cord Dia.	Catalog Numbers
Heavy duty, black and white nylon.	.230-.720" (5.8-18.3)	HBL6334CCN™
Hospital grade, black and white nylon.	.230-.720" (5.8-18.3)	HBL8319CCN

Notes: Connector bodies are not HP rated.
See Section H for complete line of hospital grade devices.
See page A-46 for technical information.
See accessories at back of this section.

Accessories

Seal-Tite® triple seal black elastomer cover for Insulgrip connector bodies when used in a cord set.	HBL6018*
Same as above except yellow elastomer.	HBL60CM18*
Closure plug, black.	HBL6019
Closure plug, yellow.	HBL60CM19
PLUGOUT® Lockout device for Hubbell connectors and others	NEW HLD

Notes: *IP55 suitability if closure plug inserted or when installed and used properly with
HBL6017 or HBL60CM17.