








HBLALU3800 and HBLALU4800 Series



Fittings for HBLALU3800 and HBLALU4800 Aluminum Raceway		Catalog Numbers	Color
Couplings (Pair) To join lengths of HBLALU3800 or HBLALU4800 base.	 	HBLALU01 A: 2.85" (72.39) B: 4.00" (101.80)	Aluminum
Grounding Adapter For connection of equipment grounding. #10-32 Locking screws included.	 	HBLALU09 A: 2.35" (59.8) B: 1.18" (30.0)	Galvanized Steel
Internal Corner Coupling For butting two raceway sections to form an internal 90° turn in a raceway run.	 	HBLALU17A A: 4.00" (101.80) B: 2.00" (50.83)	Anodized Aluminum
Blank Cover To cover 12 in. (305.00) section of raceway.	 	HBLALUBL A: 3.00" (76.20) B: 12.00" (304.80)	Anodized Aluminum
Hubbell iSTATION™ Cover For mounting Hubbell iSTATION™ Modules. For the HBLALUPB use the KPIMBZGY on page 68 with modules from page 69. For the HBLALULPBA use the IMF1GY on page 69 or any IFPxxGY plates on page 68.	 	HBLALUPB A: 3.00" (76.20) B: 12.00" (304.80) HBLALULPBA A: 3.00" (76.20) B: 12.00" (304.80)	Anodized Aluminum
Duplex Receptacle Cover For duplex receptacles and duplex communication plates.	 	HBLALUDR A: 3.00" (76.20) B: 12.00" (304.80) HBLALU34DRBM (Base Mounted Device) A: 3.00" (76.20) B: 12.00" (304.80)	Anodized Aluminum
Rectangular Style Line® Cover For Style Line rectangular duplex receptacle, GFCI, surge device or rectangular communication device.	 	HBLALUG A: 3.00" (76.20) B: 12.00" (304.80) HBLALU34GBM (Base Mounted Device) A: 3.00" (76.20) B: 12.00" (304.80)	Anodized Aluminum