


HBLALU2000 Series



Boxes

1-Gang Device Box, Standard

For standard switches and receptacles. Box base has a concentric $\frac{1}{2}$ in. and $\frac{3}{4}$ in. trade size KOs and a rectangular KO for extension to wall box.



Catalog Numbers


HBLALU2047
A: 4.54" (115.32)
B: 2.82" (71.63)
C: 1.38" (35.05)

Color

Anodized Aluminum

1-Gang Device Box, Deep

For deep switches and receptacles. Box base has a concentric $\frac{1}{2}$ in. and $\frac{3}{4}$ in. trade size KOs and a rectangular KO for extension to wall box.




HBLALU2044
A: 4.54" (115.32)
B: 2.82" (71.63)
C: 2.25" (57.15)

Anodized Aluminum

2-Gang Device Box, Standard

For standard switches and receptacles. Box base has one $\frac{1}{2}$ in. trade size KO and rectangular KO for extension to wall box.




HBLALU20472
A: 4.54" (115.32)
B: 4.64" (117.86)
C: 1.38" (35.05)

Anodized Aluminum

2-Gang Device Box, Deep

For deep switches and receptacles. Base has one $\frac{1}{2}$ in. trade size KO and rectangular KO for extension to wall box.




HBLALU20442
A: 4.54" (115.32)
B: 4.64" (117.86)
C: 2.75" (69.85)

Anodized Aluminum

Fixture Box with Solid Base

To hang fixtures. Cover takes any device with mounting screw centers of 2.75 in. (69.85), 3.5 in. (89.00) and 4.06 in. (103.00).




HBLALU2038
A: 1.38" (35.05)
B: 4.93" (125.22)

Anodized Aluminum

Fittings

Internal Elbow

For making a 90° internal turn in a raceway run.



Catalog Numbers


HBLALU2017*
A: 3.00" (76.20)
B: 3.00" (76.20)

Color

Anodized Aluminum

External Elbow

For making a 90° external turn in a raceway run.




HBLALU2018*
A: 2.91" (74.04)
B: 2.91" (74.04)

Anodized Aluminum

Flat Elbow

For making a 90° flat turn in a raceway run.




HBLALU2011*
A: 3.00" (76.20)
B: 3.00" (76.20)

Anodized Aluminum

Tee Fitting

For branch connections of right angles.



HBLALU2015*
A: 4.00" (101.60)
B: 3.40" (86.36)

Anodized Aluminum

Note: * **HBLALU2001** couplings included.