








Fittings	Catalog Numbers	Color
Blank End Fitting For closing end of raceway.	HBLALU2010B A: 1.84" (46.74) B: .91" (23.11)	Anodized Aluminum
		
Entrance End Fitting ½ in. N.P.T.	HBLALU2010A A: 1.84" (47.74) B: .91" (23.11) C: 1.51" (38.35)	Anodized Aluminum Plate Steel Fitting
		
In-Line Switch Fitting (Switch sold separately).	HBLALU2040A A: 4.12" (104.65) B: 1.84" (46.74)	Anodized Aluminum
		
In-Line Receptacle Fitting Use this fitting with single receptacle below.	HBLALU2043* A: 1.84" (46.74) B: 6.00" (152.40)	Anodized Aluminum
		
Single Receptacle - 15A Single Receptacle - 15A, Isolated Ground Single Receptacle - 20A Single Receptacle - 20A, Isolated Ground #12 AWG THHN stranded copper wires with 21 in. leads on each end.	PT1RCGY PT1RCIG PT1RGY PT1RIG A: 2.00" (50.7) B: 1.20" (30.4) C: .87" (22.2)	Gray Orange Gray Orange
		
Ground Adapter (Plated) For connection of equipment grounding conductor to provide an additional ground to raceway. Screws included.	HBLALU2009 A: 2.35" (59.8) B: 1.18" (30.0)	Galvanized Steel
		
Flush Plate Adaptor For feeding HBL2000 Raceway from an existing wall outlet. Locknut included.	HBLALU2051H A: 4.50" (114.3) B: 4.50" (114.3)	Anodized Aluminum
		

Note: * **HBLALU2001** couplings included.