



### Single Channel

- Single channel aluminum raceway.
- Satin anodized finish.
- Resists oxidation, corrosion and fading.
- Can be installed as recessed or surface mounted.
- UL Listed and CSA Certified.



### Wide Selection of Fittings

- Elbows (external, internal, flat) and tee fitting available to accommodate all types of applications.
- HBLALU2001 Coupling included with elbows and tee fitting.



### Aluminum Boxes

- Both in-line and standard boxes available.
- Hubbell Handi-Screw® eliminates difficult to install long screws for easier installation.
- Rounded corners eliminate sharp edges.
- One seam construction provides “clean” look.
- Box design allows standard wallplates to be mounted flush with virtually no perimeter profile exposed.
- Full line of metal wallplates available. See section N for selection.



### Aluminum PlugTrak® Featuring Exclusive Receptacle Design

- Satin anodized scratch resistant finish.
- Multiple spacing configurations.
- Hubbell designed and manufactured single receptacle.
- Insulation displacement wiring provides superior wire retention.
- Mates with HBLALU2000 Aluminum Raceway.
- Available in 3 ft. (0.9m), 5 ft. (1.5m) and 6 ft. (1.8m) lengths.
- Tamper-Resistant versions available.

Available in Standard, Isolated Ground (IG) and Tamper-Resistant (TR) versions.

 Tamper-Resistant



|        | Amp | Circuits  | # Single Recept. | Receptacle Spacing (in.) | Catalog Number                                                                                           |
|--------|-----|-----------|------------------|--------------------------|----------------------------------------------------------------------------------------------------------|
| 3 Foot | 15  | Single    | 6                | 6                        | <b>HBLALU20GB306</b>                                                                                     |
|        | 15  | IG/Single | 6                | 6                        | <b>HBLALU20IG306</b>                                                                                     |
|        | 15  | TR/Single | 6                | 6                        | <b>HBLALU20GB306TR</b>  |
|        | 20  | Single    | 6                | 6                        | <b>HBLALU24GB306</b>                                                                                     |
|        | 20  | IG/Single | 6                | 6                        | <b>HBLALU24IG306</b>                                                                                     |
|        | 20  | TR/Single | 6                | 6                        | <b>HBLALU24GB306TR</b>  |
| 5 Foot | 15  | Single    | 10               | 6                        | <b>HBLALU20GB506</b>                                                                                     |
|        | 15  | Single    | 5                | 12                       | <b>HBLALU20GB512</b>                                                                                     |
|        | 15  | IG/Single | 10               | 6                        | <b>HBLALU20IG506</b>                                                                                     |
|        | 15  | TR/Single | 5                | 12                       | <b>HBLALU20GB512TR</b>  |
|        | 20  | Single    | 10               | 6                        | <b>HBLALU24GB506</b>                                                                                     |
|        | 20  | Single    | 5                | 12                       | <b>HBLALU24GB512</b>                                                                                     |
|        | 20  | IG/Single | 10               | 6                        | <b>HBLALU24IG506</b>                                                                                     |
|        | 20  | TR/Single | 5                | 12                       | <b>HBLALU24GB512TR</b>  |
| 6 Foot | 15  | Single    | 12               | 6                        | <b>HBLALU20GB606</b>                                                                                     |
|        | 15  | Single    | 6                | 12                       | <b>HBLALU20GB612</b>                                                                                     |
|        | 15  | Single    | 4                | 18                       | <b>HBLALU20GB618</b>                                                                                     |
|        | 15  | Two       | 12               | 6                        | <b>HBLALU20GBA606</b>                                                                                    |
|        | 15  | Two       | 6                | 12                       | <b>HBLALU20GBA612</b>                                                                                    |
|        | 15  | Two       | 4                | 18                       | <b>HBLALU20GBA618</b>                                                                                    |
|        | 15  | IG/Single | 12               | 6                        | <b>HBLALU20IG606</b>                                                                                     |
|        | 20  | Single    | 12               | 6                        | <b>HBLALU24GB606</b>                                                                                     |
|        | 20  | Single    | 6                | 12                       | <b>HBLALU24GB612</b>                                                                                     |
|        | 20  | Single    | 4                | 18                       | <b>HBLALU24GB618</b>                                                                                     |
|        | 20  | Two       | 12               | 6                        | <b>HBLALU24GBA606</b>                                                                                    |
|        | 20  | Two       | 6                | 12                       | <b>HBLALU24GBA612</b>                                                                                    |
|        | 20  | Two       | 4                | 18                       | <b>HBLALU24GBA618</b>                                                                                    |
|        | 20  | IG/Single | 12               | 6                        | <b>HBLALU24IG606</b>                                                                                     |

Note: IG = Isolated Ground and TR = Tamper-Resistant.  
 Hubbell Aluminum PlugTrak is supplied with two HBLALU2010B blank end fittings and one HBLALU2001 coupling.

|                 | Description                                                                                                    | Catalog Number     |
|-----------------|----------------------------------------------------------------------------------------------------------------|--------------------|
| Device Boxes    | Standard 1-Gang Device Box  | <b>HBLALU2047</b>  |
|                 | Deep 1-Gang Device Box      | <b>HBLALU2044</b>  |
|                 | Standard 2-Gang Device Box  | <b>HBLALU20472</b> |
|                 | Deep 2-Gang Device Box      | <b>HBLALU20442</b> |
|                 | Round Box                   | <b>HBLALU2038</b>  |
|                 |                                                                                                                |                    |
| Elbows and Tees | External Elbow              | <b>HBLALU2018</b>  |
|                 | Internal Elbow              | <b>HBLALU2017</b>  |
|                 | Flat Elbow                 | <b>HBLALU2011</b>  |
|                 | Tee                       | <b>HBLALU2015</b>  |
| Fittings        | Cover Clip                | <b>HBLALU2006</b>  |
|                 | Supporting Clip           | <b>HBLALU2003</b>  |
|                 | Coupling                  | <b>HBLALU2001</b>  |
|                 | Entrance End Fitting      | <b>HBLALU2010A</b> |
|                 | In-Line Switch Fitting    | <b>HBLALU2040A</b> |
|                 | Blank End Fitting         | <b>HBLALU2010B</b> |

Note: See pages R-34 and R-35 for additional information.