

Micro-Quick® Control Connectors

Single Key 3 - 5 Pole Receptacles

Choose the appropriate configuration from the Selector below.

Hubbell Logic Configurator

For example, Catalog Number **MRMS13314** is derived as follows:

DEVICE TYPE	COUPLING NUT MATERIAL	BODY STYLE	KEY STYLE	POLES	CONDUCTOR TYPE	REAR THREAD STYLE
MR= Receptacle, Female MB= Receptacle, Male MF = Receptacle, Female Inverse	M = Metallic	S = Straight	1 = Single	3 4 5	3 = #22 AWG PVC Discrete Wire 4 = #18 AWG PVC Discrete Wire ♦ ♦ 3 - 4 pole only	14 = M14x1 * 25 = 1/4" NPT** 50 = 1/2" NPT* * MB Style Only **MF Style Only
↓ MR	↓ M	↓ S	↓ 1	↓ 3	↓ 3	↓ 14

Availability of specific items may vary. Consult factory for delivery. Consult the factory for additional cable lengths or cable types.

3 - 5 Pole Single Key Receptacles

Catalog numbers using #22 AWG PVC discrete wire are listed below. For #18 AWG PVC discrete wire, change the conductor type per the **Hubbell Logic** chart above.

3 - 5 Pole Single Key Receptacles- #22 AWG Discrete Wire ♦

Poles	Male Face Shown Female - mirror image	Male Receptacle Rear Thread Style		Female Inverse Receptacles Rear Thread Style
		M14 x 1	1/2" NPT	1/4" NPT
3		MBMS13314	MBMS13350	MFMS13325
4		MBMS14314	MBMS14350	MFMS14325
5		MBMS15314	MBMS15350	MFMS15325

♦ For 18 AWG discrete wire, replace the conductor type per Hubbell Logic chart above.

All receptacles available in 1 ft. length standard. For additional lengths, please consult factory.