

# Non-Metallic Raceway PP1 PremiseTrak® (Latching)

Raceway, Boxes and Fittings



| PP1 PremiseTrak® | Description                                                                                             | Color        | Length         | Without Adhesive                                                       | With Adhesive                                                            |
|------------------|---------------------------------------------------------------------------------------------------------|--------------|----------------|------------------------------------------------------------------------|--------------------------------------------------------------------------|
|                  | <b>Base and Cover</b><br>Single channel raceway.<br>Available in 5 ft. (1.5m) and 7 ft. (2.1m) lengths. | Office White | 5 ft.<br>7 ft. | <b>PP1BC5</b><br><b>PP1BC7</b><br>A: 0.77" (19.56)<br>B: 0.84" (21.34) | <b>PP1ABC5</b><br><b>PP1ABC7</b><br>A: 0.77" (19.56)<br>B: 0.84" (21.34) |



| Device Boxes | Description                                                                                                                                                                 | Color        | Catalog Number                                                                                | Description                                                                                                                                   | Color        | Catalog Number                                                                                  |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|-----------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|--------------|-------------------------------------------------------------------------------------------------|
|              | <b>1-Gang Low Profile Box</b><br>For shallow switches and receptacles. See page O-63 for recommended plate options.                                                         | Office White | <b>PDB12LP</b><br>A: 4.90" (124.46)<br>B: 3.25" (82.55)<br>C: 1.25" (31.75)                   | <b>1-Gang Deep Box</b><br>For deep devices or applications where additional room is beneficial. See page O-63 for recommended plate options.  | Office White | <b>PDB12D</b><br>A: 4.90" (124.46)<br>B: 3.25" (82.55)<br>C: 2.44" (61.98)                      |
|              | <b>1-Gang Standard Box</b><br>For standard switches and receptacles. See page O-63 for recommended plate options.                                                           | Office White | <b>PDB12S</b><br>A: 4.90" (124.46)<br>B: 3.25" (82.55)<br>C: 1.78" (45.21)                    | <b>Round Lighting Fixture Box</b><br>To hang fixtures.                                                                                        | Office White | <b>PDB12LF</b><br>A: 5.31" (134.87)<br>B: 1.29" (32.77)                                         |
|              | <b>2-Gang Deep Divided Box</b><br>For deep switches, receptacles and communication devices. See page O-63 for single gang "KP" Plate options. Comes with removable divider. | Office White | <b>PDB12TGD</b><br>A: 4.90" (124.46)<br>B: 5.06" (128.52)<br>C: 2.44" (61.98)                 | <b>2-Gang Deep Undivided Box</b><br>For low voltage applications only. Use with 2-gang "IFP" or "IMF" Plates only. See page O-63 for details. | Office White | <b>PDB12TGLV</b><br>A: 4.90" (124.46)<br>B: 5.06" (128.52)<br>C: 2.44" (61.98)                  |
| Fittings     | <b>Internal Elbow</b><br>Full capacity 1¼ in. bend radius internal elbow.                                                                                                   | Office White | <b>PP1IE*</b><br><b>PP1IEBC**</b><br>A: 2.40" (60.96)<br>B: 1.03" (26.16)<br>C: 2.40" (60.96) | <b>External Elbow</b><br>Full capacity 1¼ in. bend radius external elbow.                                                                     | Office White | <b>PP1EE*</b><br><b>PP1EEBC**</b><br>A: 4.47" (113.54)<br>B: 1.03" (26.16)<br>C: 4.47" (113.54) |
|              | <b>Flat Elbow</b><br>Full capacity 1¼ in. bend radius flat elbow.                                                                                                           | Office White | <b>PP1FE*</b><br><b>PP1FEBC**</b><br>A: 2.62" (66.55)<br>B: 2.62" (66.55)<br>C: 0.85" (21.59) | <b>Tee</b><br>Full capacity 1¼ in. bend radius tee.                                                                                           | Office White | <b>PP1TC*</b><br><b>PP1TCBC**</b><br>A: 4.22" (107.19)<br>B: 2.62" (66.55)<br>C: 0.85" (21.59)  |
|              | <b>Splice Cover</b><br>For covering potential openings where two lengths of raceway come together.                                                                          | Office White | <b>PP1SC</b><br>A: 1.09" (27.69)<br>B: 1.02" (25.91)<br>C: 0.85" (21.59)                      | <b>End Cap</b><br>For closing end of raceway.                                                                                                 | Office White | <b>PP1EC</b><br>A: 1.00" (25.40)<br>B: 0.84" (21.34)<br>C: 0.77" (19.56)                        |
|              | <b>Conduit Adapter/Ceiling Fitting</b><br>For connecting conduit to raceway. Also use for ceiling feeds. Has combination ½ in., ¾ in. and 1 in. trade size KOs.             | Office White | <b>PLP1CACF</b><br>A: 2.29" (58.17)<br>B: 3.31" (84.07)<br>C: 3.90" (99.06)                   | <b>Safety Strap</b><br>For preventing potential tampering with PP1 PremiseTrak cover. Can also be used as a splice cover.                     | Office White | <b>PP1SS</b><br>A: 0.62" (15.75)<br>B: 1.94" (49.28)<br>C: 0.86" (21.84)                        |

Note: \* Cover Only. \*\* Base and Cover.






# Non-Metallic Raceway

## PL1 LANTrak® (Latching)

Raceway, Boxes and Fittings



|              | Description                                                                                             | Color        | Length         | Without Adhesive                                                       | With Adhesive                                                            |
|--------------|---------------------------------------------------------------------------------------------------------|--------------|----------------|------------------------------------------------------------------------|--------------------------------------------------------------------------|
| PL1 LANTrak® | <b>Base and Cover</b><br>Single channel raceway.<br>Available in 5 ft. (1.5m) and 7 ft. (2.1m) lengths. | Office White | 5 ft.<br>7 ft. | <b>PL1BC5</b><br><b>PL1BC7</b><br>A: 1.04" (26.42)<br>B: 1.38" (35.05) | <b>PL1ABC5</b><br><b>PL1ABC7</b><br>A: 1.04" (26.42)<br>B: 1.38" (35.05) |
|              |                        |              |                |                                                                        |                                                                          |

|              | Description                                                                                                                                                                 | Color        | Catalog Number                                                                                | Description                                                                                                                                   | Color        | Catalog Number                                                                                  |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|-----------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|--------------|-------------------------------------------------------------------------------------------------|
| Device Boxes | <b>1-Gang Low Profile Box</b><br>For shallow switches and receptacles. See page O-63 for recommended plate options.                                                         | Office White | <b>PDB12LP</b><br>A: 4.90" (124.46)<br>B: 3.25" (82.55)<br>C: 1.25" (31.75)                   | <b>1-Gang Deep Box</b><br>For deep devices or applications where additional room is beneficial. See page O-63 for recommended plate options.  | Office White | <b>PDB12D</b><br>A: 4.90" (124.46)<br>B: 3.25" (82.55)<br>C: 2.44" (61.98)                      |
|              |                                                                                            |              |                                                                                               |                                                             |              |                                                                                                 |
|              | <b>1-Gang Standard Box</b><br>For standard switches and receptacles. See page O-63 for recommended plate options.                                                           | Office White | <b>PDB12S</b><br>A: 4.90" (124.46)<br>B: 3.25" (82.55)<br>C: 1.78" (45.21)                    | <b>Round Lighting Fixture Box</b><br>To hang fixtures.                                                                                        | Office White | <b>PDB12LF</b><br>A: 5.31" (134.87)<br>B: 1.29" (32.77)                                         |
|              |                                                                                            |              |                                                                                               |                                                             |              |                                                                                                 |
| Fittings     | <b>2-Gang Deep Divided Box</b><br>For deep switches, receptacles and communication devices. See page O-63 for single gang "KP" Plate options. Comes with removable divider. | Office White | <b>PDB12TGD</b><br>A: 4.90" (124.46)<br>B: 5.06" (128.52)<br>C: 2.44" (61.98)                 | <b>2-Gang Deep Undivided Box</b><br>For low voltage applications only. Use with 2-gang "IFP" or "IMF" Plates only. See page O-63 for details. | Office White | <b>PDB12TGLV</b><br>A: 4.90" (124.46)<br>B: 5.06" (128.52)<br>C: 2.44" (61.98)                  |
|              |                                                                                          |              |                                                                                               |                                                           |              |                                                                                                 |
|              | <b>Internal Elbow</b><br>Full capacity 1 1/4 in. bend radius internal elbow.                                                                                                | Office White | <b>PL1IE*</b><br><b>PL1IEBC**</b><br>A: 2.51" (63.75)<br>B: 1.57" (39.88)<br>C: 2.51" (63.75) | <b>External Elbow</b><br>Full capacity 1 1/4 in. bend radius external elbow.                                                                  | Office White | <b>PL1EE*</b><br><b>PL1EEBC**</b><br>A: 5.06" (128.52)<br>B: 1.57" (39.88)<br>C: 5.06" (128.52) |
|              |                                                                                          |              |                                                                                               |                                                           |              |                                                                                                 |
| Fittings     | <b>Flat Elbow</b><br>Full capacity 1 1/4 in. bend radius flat elbow.                                                                                                        | Office White | <b>PL1FE*</b><br><b>PL1FEBC**</b><br>A: 3.19" (81.03)<br>B: 3.19" (81.03)<br>C: 1.11" (28.19) | <b>Tee</b><br>Full capacity 1 1/4 in. bend radius tee.                                                                                        | Office White | <b>PL1TC*</b><br><b>PL1TCBC**</b><br>A: 4.75" (120.65)<br>B: 3.15" (80.01)<br>C: 1.11" (28.19)  |
|              |                                                                                          |              |                                                                                               |                                                           |              |                                                                                                 |
|              | <b>Splice Cover</b><br>For covering potential openings where two lengths of raceway come together.                                                                          | Office White | <b>PL1SC</b><br>A: 1.12" (28.45)<br>B: 1.55" (39.37)<br>C: 1.11" (28.19)                      | <b>End Cap</b><br>For closing end of raceway.                                                                                                 | Office White | <b>PL1EC</b><br>A: 1.00" (25.40)<br>B: 1.39" (35.31)<br>C: 1.04" (26.42)                        |
|              |                                                                                          |              |                                                                                               |                                                          |              |                                                                                                 |
|              | <b>Conduit Adapter/Ceiling Fitting</b><br>For connecting conduit to raceway. Also use for ceiling feeds. Has combination 1/2 in., 3/4 in. and 1 in. trade size KOs.         | Office White | <b>PLP1CACF</b><br>A: 2.29" (58.17)<br>B: 3.31" (84.07)<br>C: 3.90" (99.06)                   | <b>Safety Strap</b><br>For preventing potential tampering with PL1 LANTrak cover. Can also be used as a splice cover.                         | Office White | <b>PL1SS</b><br>A: 0.62" (15.75)<br>B: 2.68" (68.07)<br>C: 1.12" (28.45)                        |
|              |                                                                                          |              |                                                                                               |                                                           |              |                                                                                                 |

Note: \* Cover Only. \*\* Base and Cover.

# Non-Metallic Raceway PW1 WallTrak® Low Profile (Latching)

Raceway, Device Boxes and Fittings



Non-Metallic Raceway

| PW1 WallTrak® | Description                                                                                             | Color        | Length         | Without Adhesive                                                      | With Adhesive                                                           |
|---------------|---------------------------------------------------------------------------------------------------------|--------------|----------------|-----------------------------------------------------------------------|-------------------------------------------------------------------------|
|               | <b>Base and Cover</b><br>Single channel raceway.<br>Available in 5 ft. (1.5m) and 7 ft. (2.1m) lengths. | Office White | 5 ft.<br>7 ft. | <b>PW1BC5</b><br><b>PW1BC7</b><br>A: .50" (12.70)<br>B: 1.19" (30.23) | <b>PW1ABC5</b><br><b>PW1ABC7</b><br>A: .50" (12.70)<br>B: 1.19" (30.23) |



| Device Boxes | Description                                                                                                                                                        | Color        | Catalog Number                                                             | Description                                                                                                                                                                                                         | Color        | Catalog Number                                                              |
|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|----------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|-----------------------------------------------------------------------------|
|              | <b>1-Gang Low Profile Box</b><br>For shallow switches and receptacles.<br>See page O-63 for recommended plate options.                                             | Office White | <b>PW1LPB</b><br>A: 4.90" (124.46)<br>B: 3.25" (82.55)<br>C: 1.13" (28.70) | <b>1-Gang Deep Box</b><br>For deep devices or applications where additional room is beneficial.<br>See page O-63 for recommended plate options.                                                                     | Office White | <b>PW1DBA</b><br>A: 4.90" (124.46)<br>B: 3.25" (82.55)<br>C: 1.91" (48.51)  |
|              | <b>1-Gang Standard Box</b><br>For standard switches and receptacles.<br>See page O-63 for recommended plate options.                                               | Office White | <b>PW1SBA</b><br>A: 4.90" (124.46)<br>B: 3.25" (82.55)<br>C: 1.63" (41.40) | <b>2-Gang Deep Box</b><br>For deep devices or applications where additional room is beneficial.<br>Uses 2-gang "KP" or "IFP" Plates for power or data applications.<br>See page O-63 for recommended plate options. | Office White | <b>PW1TGB</b><br>A: 4.90" (124.46)<br>B: 5.06" (128.52)<br>C: 1.91" (48.51) |
| Fittings     | <b>Round Lighting Fixture Box</b><br>To hang fixtures.                                                                                                             | Office White | <b>PW1LFB</b><br>A: 5.31" (134.87)<br>B: 1.04" (26.52)                     |                                                                                                                                                                                                                     |              |                                                                             |
|              | <b>Internal Elbow, Cover Only</b><br>For inside surfaces at right angles.                                                                                          | Office White | <b>PW1IE</b><br>A: 1.75" (44.45)<br>B: 1.43" (36.32)<br>C: 1.75" (44.45)   | <b>External Elbow, Cover Only</b><br>For outside surfaces at right angles.                                                                                                                                          | Office White | <b>PW1EE</b><br>A: 1.50" (38.10)<br>B: 1.43" (36.32)<br>C: 1.50" (38.10)    |
|              | <b>Flat Elbow, Cover Only</b><br>For right angle turns on same surface.                                                                                            | Office White | <b>PW1FE</b><br>A: 2.18" (55.37)<br>B: 2.18" (55.37)<br>C: .60" (15.24)    | <b>Tee, Cover Only</b><br>For T-connection off PremiseTrak® Raceway.                                                                                                                                                | Office White | <b>PW1TC</b><br>A: 2.93" (74.42)<br>B: 2.18" (55.37)<br>C: .60" (15.24)     |
|              | <b>Splice Cover</b><br>For covering potential openings where two lengths of raceway come together.                                                                 | Office White | <b>PW1SC</b><br>A: 1.00" (25.40)<br>B: 1.43" (36.32)<br>C: .60" (15.24)    | <b>End Cap</b><br>For closing end of raceway.                                                                                                                                                                       | Office White | <b>PW1EC</b><br>A: 1.00" (25.40)<br>B: 1.24" (31.50)<br>C: .50" (12.70)     |
|              | <b>Conduit Adapter/Ceiling Fitting</b><br>For connecting conduit to raceway.<br>Also use for ceiling feeds. Has combination ½ in., ¾ in. and 1 in. trade size KOs. | Office White | <b>PW1CA</b><br>A: 1.40" (35.56)<br>B: 2.34" (59.44)<br>C: 3.22" (81.79)   |                                                                                                                                                                                                                     |              |                                                                             |



PW1 WallTrak® Low Profile (Latching)

# Non-Metallic Raceway

## PW2 WallTrak® (Latching)

Raceway, Device Boxes and Fittings



| PW2 WallTrak® | Description                                                                                       | Color        | Length         | Without Adhesive                                                       | With Adhesive                                                            |
|---------------|---------------------------------------------------------------------------------------------------|--------------|----------------|------------------------------------------------------------------------|--------------------------------------------------------------------------|
|               | <b>Base and Cover</b><br>Two channel raceway. Available in 5 ft. (1.5m) and 7 ft. (2.1m) lengths. | Office White | 5 ft.<br>7 ft. | <b>PW2BC5</b><br><b>PW2BC7</b><br>A: 1.04" (26.42)<br>B: 2.12" (53.85) | <b>PW2ABC5</b><br><b>PW2ABC7</b><br>A: 1.04" (26.42)<br>B: 2.12" (53.85) |

| Device Boxes | Description                                                                                                                                                                                       | Color        | Catalog Number                                                                                  | Description                                                                                                                                                                                                                                  | Color        | Catalog Number                                                                                  |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|-------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|-------------------------------------------------------------------------------------------------|
|              | <b>1-Gang Low Profile Box</b><br>For shallow switches and receptacles. See page O-63 for recommended plate options.                                                                               | Office White | <b>PDB12LP</b><br>A: 4.90" (124.46)<br>B: 3.25" (82.55)<br>C: 1.25" (31.75)                     | <b>Round Lighting Fixture Box</b><br>To hang fixtures.                                                                                                                                                                                       | Office White | <b>PDB12LF</b><br>A: 5.31" (134.87)<br>B: 1.29" (32.77)                                         |
|              | <b>1-Gang Standard Box</b><br>For standard switches and receptacles. See page O-63 for recommended plate options. If using dual services, the PDB1DIV must be ordered.                            | Office White | <b>PDB12S</b><br>A: 4.90" (124.46)<br>B: 3.25" (82.55)<br>C: 1.78" (45.21)                      | <b>2-Gang Deep Undivided Box</b><br>For low voltage applications only. Use with 2-gang "IFP" or "IMF" Plates only. See page O-63 for details.                                                                                                | Office White | <b>PDB12TGLV</b><br>A: 4.90" (124.46)<br>B: 5.06" (128.52)<br>C: 2.44" (61.98)                  |
|              | <b>1-Gang Deep Box</b><br>For deep devices or applications where additional room is beneficial. See page O-63 for recommended plate options. If using dual services, the PDB1DIV must be ordered. | Office White | <b>PDB12D</b><br>A: 4.90" (124.46)<br>B: 3.25" (82.55)<br>C: 2.44" (61.98)                      | <b>2-Gang Deep Divided Box</b><br>For deep devices or applications where additional room is beneficial. See page O-63 for single gang "KP" Plate options. Comes with removable divider. If using dual services, the PDB2DIV must be ordered. | Office White | <b>PDB12TGD</b><br>A: 4.90" (124.46)<br>B: 5.06" (128.52)<br>C: 2.44" (61.98)                   |
|              | <b>1-Gang Divider</b><br>For use with PDB12S and PDB12D 1-gang boxes. Required when two services are passing through box.                                                                         | Office White | <b>PDB1DIV</b><br>A: 2.79" (70.86)<br>B: 1.40" (35.56)<br>C: 0.94" (23.88)                      | <b>2-Gang Divider</b><br>For use with PDB12TGD 2-gang box only. Required when two services are passing through box and mounting devices perpendicular to raceway.                                                                            | Office White | <b>PDB2DIV</b><br>A: 4.62" (117.35)<br>B: 2.76" (70.10)<br>C: 0.94" (23.88)                     |
|              | <b>Internal Elbow</b><br>Full capacity 1 1/4 in. bend radius internal elbow.                                                                                                                      | Office White | <b>PW2IE*</b><br><b>PW2IEBC**</b><br>A: 2.83" (71.88)<br>B: 2.32" (58.93)<br>C: 2.83" (71.88)   | <b>External Elbow</b><br>Full capacity 1 1/4 in. bend radius external elbow.                                                                                                                                                                 | Office White | <b>PW2EE*</b><br><b>PW2EEBC**</b><br>A: 5.00" (127.00)<br>B: 2.32" (58.93)<br>C: 5.00" (127.00) |
|              | <b>Flat Elbow</b><br>Full capacity 1 1/4 in. bend radius flat elbow.                                                                                                                              | Office White | <b>PW2FE*</b><br><b>PW2FEBC**</b><br>A: 3.94" (100.08)<br>B: 3.94" (100.08)<br>C: 1.11" (28.19) | <b>Tee</b><br>Full capacity 1 1/4 in. bend radius tee.                                                                                                                                                                                       | Office White | <b>PW2TC*</b><br><b>PW2TCBC**</b><br>A: 5.42" (137.67)<br>B: 3.91" (99.31)<br>C: 1.90" (48.26)  |
|              | <b>Splice Cover</b><br>For covering potential openings where two lengths of raceway come together.                                                                                                | Office White | <b>PW2SC</b><br>A: 1.11" (28.19)<br>B: 2.30" (58.42)<br>C: 1.11" (28.19)                        | <b>Safety Strap</b><br>For preventing potential tampering with PW2 WallTrak Cover. Can also be used as a splice cover.                                                                                                                       | Office White | <b>PW2SS</b><br>A: 0.62" (15.75)<br>B: 3.43" (87.12)<br>C: 1.12" (28.45)                        |
|              | <b>Conduit Adapter/Ceiling Fitting</b><br>For connecting conduit to raceway. Also use for ceiling feeds. Has combination 1/2 in., 3/4 in. and 1 in. trade size KOs.                               | Office White | <b>PW2CACF</b><br>A: 4.18" (106.17)<br>B: 3.32" (84.33)<br>C: 4.20" (106.68)                    | <b>Reducer</b><br>Reduces from PW2 WallTrak Raceway to one or two PP1 PremiseTrak Raceway(s).                                                                                                                                                | Office White | <b>PW2RED</b><br>A: 1.62" (41.15)<br>B: 2.40" (60.96)<br>C: 1.15" (29.21)                       |
|              | <b>End Cap</b><br>For closing end of PW2 WallTrak Raceway.                                                                                                                                        | Office White | <b>PW2EC</b><br>A: 1.00" (25.40)<br>B: 2.14" (54.36)<br>C: 1.04" (26.42)                        |                                                                                                                                                                                                                                              |              |                                                                                                 |

Note: \* Cover Only. \*\* Base and Cover.

# Non-Metallic Raceway




## PB2 BaseTrak®

Raceway, Device Boxes and Fittings



| PB2 BaseTrak® | Description                                                                                                                                                                 | Color           | Length          | Catalog Number                                                         | Description                                                                                                                                                                                          | Color           | Length          | Catalog Number                                        |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|-----------------|------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|-----------------|-------------------------------------------------------|
|               | <b>Base</b><br>Two channel raceway. Available in 5 ft. (1.5m) and 10 ft. (3m) lengths.<br><br>Assembled cover and base dimensions.<br>W: 4.50" (114.30)<br>H: 1.63" (41.40) | Office<br>White | 5 ft.<br>10 ft. | <b>PB2B5</b><br><b>PB2B10</b><br>A: 1.42" (36.07)<br>B: 4.50" (114.30) | <b>Cover</b><br>Cover allows access to multiple channels. Available in 5 ft. (1.5m) and 10 ft. (3m) lengths.                                                                                         | Office<br>White | 5 ft.<br>10 ft. | <b>PB2C5</b><br><b>PB2C10</b><br>B: 4.50" (114.30)    |
|               |                                                                                            |                 |                 |                                                                        | <b>Split Cover</b><br>Cover allows separation of channels and access to a single channel. Available in 5 ft. (1.5m) and 10 ft. (3m) lengths. Two split covers are required for each raceway section. | Office<br>White | 5 ft.<br>10 ft. | <b>PB2SPL5</b><br><b>PB2SPL10</b><br>B: 2.22" (56.39) |
|               |                                                                                                                                                                             |                 |                 |                                                                        |                                                                                                                   |                 |                 |                                                       |

| Device Boxes | Description                                                                                                                                              | Color           | Catalog Number                                                                |
|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|-------------------------------------------------------------------------------|
|              | <b>2-Gang In-Line Box</b><br>For switches, receptacles and communication devices. Provides flush look. See page O-63 for recommended "KP" Plate options. | Office<br>White | <b>PB2IND2G</b><br>A: 7.66" (194.56)<br>B: 4.74" (120.40)<br>C: 1.84" (46.74) |
|              |                                                                        |                 |                                                                               |

| Fittings | Description                                                                                                                                                                     | Color           | Catalog Number                                                                 | Description                                                                                                            | Color           | Catalog Number                                                                 |
|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|--------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|-----------------|--------------------------------------------------------------------------------|
|          | <b>Internal Elbow, Base and Cover</b><br>Full capacity 1¼ in. bend radius internal elbow.                                                                                       | Office<br>White | <b>PB3IEBCA</b><br>A: 4.36" (110.74)<br>B: 4.72" (119.89)<br>C: 4.36" (110.74) | <b>External Elbow, Base and Cover</b><br>Full capacity 1¼ in. bend radius external elbow.                              | Office<br>White | <b>PB3EEBCA</b><br>A: 6.48" (164.59)<br>B: 4.72" (119.89)<br>C: 6.48" (164.59) |
|          |                                                                                               |                 |                                                                                |                                     |                 |                                                                                |
|          | <b>Flat Elbow, Base and Cover</b><br>Full capacity 1¼ in. bend radius flat elbow.                                                                                               | Office<br>White | <b>PB3FEBCA</b><br>A: 7.64" (194.66)<br>B: 7.64" (194.66)<br>C: 1.71" (43.43)  | <b>Tee, Base and Cover</b><br>Full capacity 1¼ in. bend radius tee.                                                    | Office<br>White | <b>PB3TCBCA</b><br>A: 7.37" (187.20)<br>B: 7.08" (179.83)<br>C: 2.72" (69.09)  |
|          |                                                                                              |                 |                                                                                |                                    |                 |                                                                                |
|          | <b>Splice Cover</b><br>For covering potential openings where two lengths of raceway come together.                                                                              | Office<br>White | <b>PB3SC</b><br>A: 1.56" (39.62)<br>B: 4.74" (120.40)<br>C: 1.69" (42.93)      | <b>Safety Strap</b><br>For preventing potential tampering with PB2 BaseTrak Cover. Can also be used as a splice cover. | Office<br>White | <b>PB3SS</b><br>A: 1.50" (38.10)<br>B: 6.01" (152.65)<br>C: 1.74" (44.20)      |
|          |                                                                                              |                 |                                                                                |                                   |                 |                                                                                |
|          | <b>Conduit Adapter/Ceiling Fitting</b><br>For connecting conduit to raceway. Also use for ceiling feeds. Has combination ½ in., ¾ in., 1 in., 1¼ in. and 1½ in. trade size KOs. | Office<br>White | <b>PB2CACF</b><br>A: 4.72" (119.89)<br>B: 5.22" (132.70)<br>C: 6.30" (160.02)  | <b>Reducer</b><br>Reduces from PB2 BaseTrak Raceway to PW2 WallTrak Raceway.                                           | Office<br>White | <b>PB3REDA</b><br>A: 3.50" (88.90)<br>B: 4.72" (119.89)<br>C: 1.73" (43.94)    |
|          |                                                                                              |                 |                                                                                |                                   |                 |                                                                                |
|          | <b>Transition Fitting</b><br>Transitions horizontal PB2 BaseTrak to vertical PW2 WallTrak, PL1 LANTrak or PP1 PremiseTrak.                                                      | Office<br>White | <b>PB3TRBC</b><br>A: 3.22" (81.79)<br>B: 7.28" (184.91)<br>C: 2.42" (61.47)    | <b>Surface Panel Connector</b><br>For connecting PB2 Raceway with surface type panel boxes.                            | Office<br>White | <b>PB3SPCA</b><br>A: 2.22" (56.39)<br>B: 5.66" (143.76)<br>C: 1.60" (40.64)    |
|          |                                                                                              |                 |                                                                                |                                   |                 |                                                                                |
|          | <b>End Cap</b><br>For closing end of PB2 BaseTrak Raceway.                                                                                                                      | Office<br>White | <b>PB3ECA</b><br>A: 2.02" (51.31)<br>B: 4.68" (118.97)<br>C: 1.72" (43.69)     | <b>Wire Clip</b><br>For holding conductors in place.                                                                   | Office<br>White | <b>PB2WC</b>                                                                   |
|          |                                                                                              |                 |                                                                                |                                   |                 |                                                                                |

Dimensions in Inches (mm)

www.hubbell-wiring.com



Wiring Device-Kellems

O-59

Non-Metallic Raceway

PB2 BaseTrak®

## Non-Metallic Raceway

**PB3 BaseTrak®**

Raceway, Device Boxes and Fittings



| PB3 BaseTrak® | Description                                                                                                                                                                                    |  | Color        | Length                                                                                            | Catalog Number                                                                                                      |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--------------|---------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
|               | <b>Base and Cover</b><br>Three channel raceway. Available in 5 ft. (1.5m) and 10 ft. (3m) lengths.                                                                                             |  | Office White | 5 ft.<br>10 ft.                                                                                   | <b>PB3BC5</b><br><b>PB3BC10</b><br>A: 1.63" (41.40)<br>B: 4.50" (114.30)                                            |
| Device Boxes  | <b>Full Capacity Boxes</b><br>1-, 2- and 3-Gang boxes that allows full capacity from PB3 Raceway to box for either power or datacom applications. See page O-63 for recommended plate options. |  | Office White | <b>PB3FCIB (1-Gang)</b><br>A: 4.38" (111.25)<br>B: 4.80" (121.92)<br>C: 3.17" (80.52)             | <b>PB3FCIB2G (2-Gang)</b><br>A: 7.20" (182.88)<br>B: 4.80" (121.92)<br>C: 3.17" (80.52)                             |
|               | <b>1-Gang In-Line Box</b><br>For switches, receptacles and communication devices. Provides flush look. See page O-63 for recommended plate options.                                            |  | Office White | <b>PB3IND</b><br>A: 4.90" (124.46)<br>B: 3.25" (82.55)<br>C: 1.25" (31.75)                        | <b>PB3IND2G</b><br>A: 4.90" (124.46)<br>B: 3.25" (82.55)<br>C: 2.44" (61.98)                                        |
|               | <b>Internal Elbow</b><br>Full capacity 1 1/4 in. bend radius internal elbow.                                                                                                                   |  | Office White | <b>PB3IE*</b><br><b>PB3IEBCA**</b><br>A: 4.36" (110.74)<br>B: 4.72" (119.89)<br>C: 4.36" (110.74) | <b>PB3EE*</b><br><b>PB3EEBCA**</b><br>A: 6.48" (164.59)<br>B: 4.72" (119.89)<br>C: 6.48" (164.59)                   |
|               | <b>Flat Elbow</b><br>Full capacity 1 1/4 in. bend radius flat elbow.                                                                                                                           |  | Office White | <b>PB3FE*</b><br><b>PB3FEBCA**</b><br>A: 7.64" (194.66)<br>B: 7.64" (194.66)<br>C: 1.71" (43.43)  | <b>PB3TCBCA**</b><br>A: 7.37" (187.20)<br>B: 7.08" (179.83)<br>C: 2.72" (69.09)                                     |
| Fittings      | <b>Splice Cover</b><br>For covering potential openings where two lengths of raceway come together.                                                                                             |  | Office White | <b>PB3SC*</b><br>A: 1.56" (39.62)<br>B: 4.74" (120.40)<br>C: 1.69" (42.93)                        | <b>Safety Strap</b><br>Prevents potential tampering with PB3 BaseTrak Cover. Can also be used as a splice cover.    |
|               | <b>Conduit Adapter/Ceiling Fitting</b><br>For connecting conduit to raceway. Also use for ceiling feeds. Has combination 1/2 in., 3/4 in., 1 in., 1 1/4 in. and 1 1/2 in. trade size KOs.      |  | Office White | <b>PB3CACF**</b><br>A: 4.72" (119.89)<br>B: 5.22" (132.70)<br>C: 6.30" (160.02)                   | <b>Reducer</b><br>Reduces from PB3 BaseTrak Raceway to PW2 WallTrak Raceway.                                        |
|               | <b>Transition Fitting</b><br>Transitions horizontal PB3 BaseTrak to vertical PW2 WallTrak, PL1 LANTrak or PP1 PremiseTrak.                                                                     |  | Office White | <b>PB3TRBC**</b><br>A: 3.22" (81.79)<br>B: 7.28" (184.91)<br>C: 2.42" (61.47)                     | <b>Transition Fitting</b><br>Transitions from BT3 (old style) BaseTrak Raceway to PB3 (new style) BaseTrak Raceway. |
|               | <b>Surface Panel Connector</b><br>For connecting PB3 Raceway with surface type panel boxes.                                                                                                    |  | Office White | <b>PB3SPCA*</b><br>A: 2.22" (56.39)<br>B: 5.66" (143.76)<br>C: 1.60" (40.64)                      | <b>End Cap</b><br>For closing end of PB3 BaseTrak Raceway.                                                          |
|               | <b>Wire Clip</b><br>For holding conductors in place.                                                                                                                                           |  | Office White | <b>PB3WC</b>                                                                                      |                                                                                                                     |
|               |                                                                                                                                                                                                |  |              |                                                                                                   |                                                                                                                     |
|               |                                                                                                                                                                                                |  |              |                                                                                                   |                                                                                                                     |

Note: \* Cover Only. \*\* Base and Cover.

# Non-Metallic Raceway PS3 Super BaseTrak® Raceway, Device Boxes and Fittings



| PS3 BaseTrak® | Description                                                                                                                                                                                    | Color        | Length                                                                                           | Catalog Number                                                                                                         |                                                                                                                  |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|--------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------|
|               | <b>Base and Cover</b><br>Three channel raceway. Available in 5 ft. (1.5m) and 10 ft. (3m) lengths.                                                                                             | Office White | 5 ft.<br>10 ft.                                                                                  | <b>PS3BC5</b><br><b>PS3BC10</b><br>A: 1.97" (50.04)<br>B: 6.70" (170.18)                                               |                                                                                                                  |
| Device Boxes  | <b>Full Capacity Boxes</b><br>1-, 2- and 3-Gang boxes that allows full capacity from PS3 Raceway to box for either power or datacom applications. See page O-63 for recommended plate options. | Office White | <b>PS3FCIB (1-Gang)</b><br>A: 4.38" (111.25)<br>B: 6.95" (176.53)<br>C: 3.46" (87.88)            | <b>PS3FCIB2G (2-Gang)</b><br>A: 7.20" (182.88)<br>B: 6.95" (176.53)<br>C: 3.46" (87.88)                                | <b>PS3FCIB3G (3-Gang)</b><br>A: 9.96" (252.98)<br>B: 6.95" (176.53)<br>C: 3.46" (87.88)                          |
|               | <b>3-Gang In-Line Box</b><br>For any combination of power and datacom applications. Provides flush look. See page O-63 for recommended plate options.                                          | Office White | <b>PS3IND</b><br>A: 7.00" (177.80)<br>B: 6.95" (176.53)<br>C: 2.28" (57.91)                      |                                                                                                                        |                                                                                                                  |
|               | <b>Internal Elbow</b><br>Full capacity 1¼ in. bend radius internal elbow.                                                                                                                      | Office White | <b>PS3IE*</b><br><b>PS3IEBC**</b><br>A: 4.36" (110.74)<br>B: 6.93" (176.02)<br>C: 4.36" (110.74) | <b>External Elbow</b><br>Full capacity 1¼ in. bend radius external elbow.                                              | Office White<br><b>PS3EE*</b><br><b>PS3EEBC**</b><br>A: 6.81" (172.97)<br>B: 6.93" (176.02)<br>C: 6.81" (172.97) |
|               | <b>Flat Elbow</b><br>Full capacity 1¼ in. bend radius flat elbow.                                                                                                                              | Office White | <b>PS3FE*</b><br><b>PS3FEBC**</b><br>A: 9.85" (250.19)<br>B: 9.85" (250.19)<br>C: 2.08" (52.83)  | <b>Tee</b><br>Full capacity 1¼ in. bend radius tee.                                                                    | Office White<br><b>PS3TCBC**</b><br>A: 10.00" (254.00)<br>B: 9.68" (245.87)<br>C: 3.30" (83.82)                  |
| Fittings      | <b>Splice Cover</b><br>For covering potential openings where two lengths of raceway come together.                                                                                             | Office White | <b>PS3SC*</b><br>A: 1.56" (39.62)<br>B: 6.95" (176.53)<br>C: 2.03" (51.62)                       | <b>Safety Strap</b><br>Prevents potential tampering with PS3 Super BaseTrak cover. Can also be used as a splice cover. | Office White<br><b>PS3SS*</b><br>A: 1.50" (38.10)<br>B: 8.24" (209.30)<br>C: 2.08" (52.85)                       |
|               | <b>Conduit Adapter/Ceiling Fitting</b><br>For connecting conduit to raceway. Also use for ceiling feeds. Has combination ½ in., ¾ in., 1 in., 1¼ in. and 1½ in. trade size KOs.                | Office White | <b>PS3CACF**</b><br>A: 6.93" (176.02)<br>B: 4.32" (109.73)<br>C: 6.29" (159.77)                  | <b>Reducer</b><br>Reduces from PS3 Super BaseTrak Raceway to PB3 BaseTrak Raceway.                                     | Office White<br><b>PS3RED**</b><br>A: 4.81" (122.17)<br>B: 6.93" (176.02)<br>C: 2.05" (52.07)                    |
|               | <b>Surface Panel Connector</b><br>To connect PS3 Raceway with surface type panel boxes.                                                                                                        | Office White | <b>PS3SPC*</b><br>A: 1.00" (25.40)<br>B: 7.87" (199.90)<br>C: 2.54" (64.52)                      | <b>End Cap</b><br>For closing end of PS3 Super BaseTrak Raceway.                                                       | Office White<br><b>PS3EC*</b><br>A: 1.50" (38.10)<br>B: 6.88" (174.75)<br>C: 2.06" (52.32)                       |
|               | <b>Wire Clip</b><br>For holding conductors in place.                                                                                                                                           | Office White | <b>PS3WC</b>                                                                                     |                                                                                                                        |                                                                                                                  |

Note: \* Cover Only. \*\* Base and Cover.

Dimensions in Inches (mm)

www.hubbell-wiring.com



Wiring Device-Kellems

O-61