






End Fittings	Description	Material	Catalog Number	Description	Material	Catalog Number
	Entrance End Fitting ½ in. NPT steel fitting.	Anodized Aluminum Plate	HBLALU2010A A: 1.84" (47.74) B: .91" (23.11) C: 1.51" (38.35)	Blank End Fitting For closing end of raceway.	Anodized Aluminum	HBLALU2010B A: 1.84" (46.74) B: .91" (23.11)
						

Fittings	Cover Clip			Wire Clip		
	Description	Material	Catalog Number	Description	Material	Catalog Number
	Cover Clip Use to cover potential openings where two pieces of HBLALU2000 Raceway cover come together.	Stainless Steel	HBLALU2006 A: 1.00" (25.40)	Wire Clip For holding conductors in place.	Anodized Aluminum	HBLALU2000WC A: .44" (11.20)
						
	Flush Plate Adaptor For feeding HBL2000 Raceway from an existing wall outlet. Locknut included.			Coupling (Pair) For joining lengths of HBLALU2000 Raceway.		
	Anodized Aluminum	HBLALU2051H A: 4.50" (114.3) B: 4.50" (114.3)		Aluminum	HBLALU2001 A: 1.67" (42.42) B: 1.67" (42.42)	
						

Devices and In-Line Fittings	Description	Material	Catalog Number	Description	Material	Catalog Number
	In-Line Receptacle Fitting Use this fitting with single receptacle below.	Anodized Aluminum	HBLALU2043* A: 1.84" (46.74) B: 6.00" (152.40)	In-Line Switch Fitting (Switch sold separately).	Anodized Aluminum	HBLALU2040A A: 4.12" (104.65) B: 1.84" (46.74)
						
	Single Receptacle 15A 125V 15A 125V, Isolated Ground 20A 125V 20A 125V, Isolated Ground #12 AWG THHN stranded copper wires with 21 in. leads on each end.	Gray Orange Gray Orange	PT1RCGY PT1RCIG PT1RGY PT1RIG A: 2.00" (50.7) B: 1.20" (30.4) C: .87" (22.2)	Ground Adapter (Plated) For connection of equipment grounding conductor to provide an additional ground to raceway. Screws included.	Steel**	HBLALU2009 A: 2.35" (59.8) B: 1.18" (30.0)
						
				Supporting Clip For mounting lengths of HBLALU2000 Raceway at any point. Mount with #6 flat head fastener. Has set screw for locking to raceway. Raceway must be screwed to the wall for secure fastening.	Stainless Steel	HBLALU2003 A: 2.00" (50.80)
						

Note: *HBLALU2001 couplings included.
 **Galvanized Steel.

Dimensions in Inches (mm)