

2X2 Flush Duplex FRPT, One-Piece Units (PT7FSD)

Description	Color	Catalog No.	Description	Color/Material	Catalog No.
Flush Poke-Through	Black Brown Gray Ivory Gray Ivory	PT7FSDBLA PT7FSDBRA PT7FSDGYA PT7FSDIA PT7IGFSDGYA* PT7IGFSDIA*	Flush Brass Poke-Through	All Brass Black/Brass All Brass	PT7FSDBRS2A PT7FSDBRS3A PT7IGFSDBRSA*
Complete assembled unit includes: • Pre-wired 20A duplex receptacle • Non-metallic flip lid cover with (2) 1/2 in. diameter low voltage feed-through holes • Painted aluminum flange			Complete assembled unit includes: • Pre-wired 20A duplex receptacle • All brass or black non-metallic cover option • Flip lid cover with (2) 1/2 in. diameter low voltage feed-through holes • Solid brass flange		



Note: *Includes pre-wired 20A isolated ground duplex receptacle.

Flush FRPT, Two-Piece Units

Description	Catalog No.
Multi-Channel Through-Floor Fitting with (1) 3/4 in. E.M.T. stem for power and (2) 1/2 in. low voltage feed-through holes.	PT7FSD (with Junction Box) PT73SD (without Junction Box)
Specifications: • 1 – 4 hour fire rating (1 – 3 hour for steel floor units and concrete topping, D900 Series Design) • For 2 1/4 in. to 7 in. floor thickness • UL installation spacing – minimum 2 ft. on center and not more than one per 65 sq. ft. of floor area	



Service Fittings

Description	Color	Catalog No.	Description	Color/Material	Catalog No.
Flush Aluminum Service Fitting	Black Brown Gray Ivory	FRFBLA FRFBRA FRFGYA FRFIA	2X2 Poke-Through	Solid Brass	FRFBR2A
Complete assembled unit includes: • Pre-wired 20A duplex receptacle • Non-metallic flip lid cover with (2) 1/2 in. diameter low voltage feed-through holes • Painted aluminum flange			Complete assembled unit includes: • Pre-wired 20A duplex receptacle • Solid brass flip lid cover with (2) 1/2 in. diameter low voltage feed-through holes • Solid brass flange		



Accessories

Description	Color	Catalog No.	Description	Color/Material	Catalog No.
Non-Metallic Replacement Covers	Black Brown Gray Ivory	PFBRCBLA PFBRCBRA PFBRCGYA PFBRCIA	All Brass Replacement Covers	Solid Brass	BRS2RCA



Note: See page Q28 for 3-inch FRPT accessories.

ScrubShield®

Complies with UL514 A & C