

## Hubbell SystemOne Sub-Plates

| Description                                                                                                                                                                                         | Catalog Number                                                                                          | Description                                                                                                                                                                            | Catalog Number                                                                                                                                                  | Description                                                                                                                                                                                                        | Catalog Number                                                                                                                                                     |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Style Line® Decorator/GFCI</b><br>(2) Style Line® Decorator openings for power and/or datacom applications.                                                                                      | <br><b>S1SP</b>        | <b>Duplex/Duplex</b><br>(2) Duplex openings for power and/or datacom applications.                                                                                                     | <br><b>S1SPDU</b>                                                             | <b>Duplex/Style Line® Decorator</b><br>(1) Duplex and (1) Style Line® Decorator opening for power and/or datacom applications.                                                                                     | <br><b>S1SPDUSL</b>                                                             |
| ③ Non-Metallic ③.5 Metal                                                                                                                                                                            |                                                                                                         | ③ Non-Metallic ③.5 Metal                                                                                                                                                               |                                                                                                                                                                 | ③ Non-Metallic ③.5 Metal                                                                                                                                                                                           |                                                                                                                                                                    |
| <b>Hubbell 4 X 4</b><br>(4) 20A, 125V receptacles.<br>(4) Keystone openings for Hubbell jacks or flush A/V connectors. Power can be wired as single or two circuit with isolated ground capability. | <br><b>S1SP4X4</b>     | <b>Carpet Furniture Feed Cover/Flange*</b><br>(1) 3/4" and (1) 1 1/2" N.P.T. access holes for power and/or datacom applications. Universal Cover not required. Includes carpet flange. | <br><b>S1SPFFAL</b><br><b>S1SPFFBRS</b><br><b>S1SPFFBL</b><br><b>S1SPFFGY</b> | <b>Tile Furniture Feed Cover/Flange*</b><br>(1) 3/4" and (1) 1 1/2" N.P.T. access holes for power and/or datacom applications. Universal Cover not required. Includes tile flange.                                 | <br><b>S1SPFFTAL</b><br><b>S1SPFFTBR</b><br><b>S1SPFFTBL</b><br><b>S1SPFTGY</b> |
| ④<br>Provided with 15 ft. wire leads<br>Provided with 30 ft. wire leads                                                                                                                             | <b>S1SP4X415</b><br><b>S1SP4X430</b>                                                                    | ③ Non-Metallic Aluminum Fin.<br>③.5 Metal Brass Fin.<br>Black<br>Gray                                                                                                                  |                                                                                                                                                                 | ③ Non-Metallic Aluminum Fin.<br>③.5 Metal Brass Fin.<br>Black<br>Gray                                                                                                                                              |                                                                                                                                                                    |
| <b>Single Receptacle + Data</b><br>Opening for 20 or 30A Twist-Lock® receptacle (1.56" OD) and (2) Keystone openings for Hubbell jacks or flush A/V connectors.                                     | <br><b>S1SPTL</b>      | <b>Hubbell DataCom + Power</b><br>(1) 20A, 125V receptacle and 3 unit recessed iSTATION™ opening for data, voice, and A/V applications.                                                | <br><b>S1SP3IM</b>                                                            | <b>Hubbell DataCom + Duplex</b><br>(1) Duplex opening, (2) flush Keystone openings and 1.5 unit recessed iSTATION™ opening for data, voice and A/V applications.                                                   | <br><b>S1SPDU2IM</b>                                                            |
| ④                                                                                                                                                                                                   |                                                                                                         | ⑤                                                                                                                                                                                      |                                                                                                                                                                 | ⑤                                                                                                                                                                                                                  |                                                                                                                                                                    |
| <b>Hubbell DataCom + Style Line® Decorator</b><br>(1) Style Line® Decorator opening, (2) flush Keystone openings and 1.5 unit recessed iSTATION™ opening for data, voice and A/V applications.      | <br><b>S1SPSL2IM</b>   | <b>Hubbell DataCom</b><br>1 unit flush iSTATION™ opening and 3 unit recessed iSTATION™ opening for data, voice, and A/V applications.                                                  | <br><b>S1SP4IM</b>                                                            | <b>Active Multimedia + Power</b><br>Single 20A, 125V receptacle; (2) flush Keystone openings; (1) rectangular Style Line® Decorator opening to accommodate active multimedia modules or low voltage outlet frames. | <br><b>S1SPAMM20</b>                                                            |
| ⑤                                                                                                                                                                                                   |                                                                                                         | ③.5                                                                                                                                                                                    |                                                                                                                                                                 | ⑤                                                                                                                                                                                                                  |                                                                                                                                                                    |
| <b>Extron® or FSR + Power</b><br>(1) 20A, 125V receptacle. Recessed opening for (3) single Extron® MAAP series adapter plates or FSR IPS plates.                                                    | <br><b>S1SPEXT1</b>  | <b>Extron® or FSR + Power</b><br>(1) 20A, 125V receptacle. Recessed opening for (1) single Extron® MAAP and (2) single AAP series adapter plates or FSR IPS plates.                    | <br><b>S1SPEXT2</b>                                                         | <b>Extron® or FSR Single-Service</b><br>Recessed opening for (2) single Extron® MAAP and (2) single AAP series adapter plates or FSR IPS plates.                                                                   | <br><b>S1SPEXT3</b>                                                           |
| ④                                                                                                                                                                                                   |                                                                                                         | ④                                                                                                                                                                                      |                                                                                                                                                                 | ④.5                                                                                                                                                                                                                |                                                                                                                                                                    |
| <b>Extron® AAP + Power</b><br>(1) 20A, 125V receptacle. (2) flush Keystone and recessed opening for (2) single Extron® AAP Series adapter plates.                                                   | <br><b>S1SPEXT4</b>  | <b>Ortronics Series II® + Power</b><br>(1) 20A, 125V receptacle. Recessed opening for (3) 1 unit Ortronics Series II® modules.                                                         | <br><b>S1SPORT</b>                                                          | <b>Ortronics TracJack® + Power</b><br>(1) 20A, 125V receptacle. Recessed bezel for (6) Ortronics TracJack® modules.                                                                                                | <br><b>S1SPTRAC</b>                                                           |
| ④                                                                                                                                                                                                   |                                                                                                         | ⑤                                                                                                                                                                                      |                                                                                                                                                                 | ⑤                                                                                                                                                                                                                  |                                                                                                                                                                    |
| <b>Panduit Mini Com® 4 X 4</b><br>(4) 20A, 125V receptacles. (4) Openings for Panduit Mini-Com Connectivity.                                                                                        | <br><b>S1SP4X4PA</b> | <b>SYSTIMAX® 4 X 4</b><br>(4) 20A, 125V receptacles. (4) Openings for SYSTIMAX® Connectivity.                                                                                          | <br><b>S1SP4X4SYS</b>                                                       | <b>Siemon MAX® + Power</b><br>(1) 20A, 125V receptacle. Recessed bezel for (6) Siemon MAX® modules.                                                                                                                | <br><b>S1SPMAX</b>                                                            |
| ④                                                                                                                                                                                                   |                                                                                                         | ④                                                                                                                                                                                      |                                                                                                                                                                 | ⑤                                                                                                                                                                                                                  |                                                                                                                                                                    |

③ Signifies minimum depth of concrete pour in inches for Metal Floor Boxes (**S1CFB**, **S1SFB** and **S1SFBV**) and Non-Metallic Floor Box (**S1PFB**).  
\*Furnished with two screw-in flexible metal conduit connectors.

## Sub-Plate Accessories

| Description                                                                                                                                                           | Catalog Number                                                                                          | Description                                                                                                                       | Catalog Number                                                                                           |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|
| <b>Replacement Threaded Conduit Plugs</b><br>Used with <b>S1SPFFx</b> and <b>S1SPFTx</b> ONLY.<br>Sub-plate is supplied with plugs.                                   |                                                                                                         |                                                |                                                                                                          |
| <b>6-Port Replacement Data Frames</b><br>Used with open systems sub-plates. Sub-plate is supplied with data frame. Siemon MAX® for use with <b>S1SPMAX</b> sub-plate. | <br><b>S1DFMAX</b> | <b>Ortronics TracJack® for use with S1SPTRAC sub-plate.</b>                                                                       | <br><b>S1DFTRAC</b> |
| <b>Black Style Line® blank frame.</b>                                                                                                                                 | <br><b>2100BK</b>  |                                                                                                                                   |                                                                                                          |
| 1 1/2" Aluminum Fin. <b>S1FP15AL</b><br>1 1/2" Brass Fin. <b>S1FP15BRS</b><br>1 1/2" Black <b>S1FP15BL</b><br>1 1/2" Gray <b>S1FP15GY</b>                             |                                                                                                         | 3/4" Aluminum Fin. <b>S1FP34AL</b><br>3/4" Brass Fin. <b>S1FP34BRS</b><br>3/4" Black <b>S1FP34BL</b><br>3/4" Gray <b>S1FP34GY</b> |                                                                                                          |

Extron® is a registered trademark of Extron Electronics. MAX® is a registered trademark of The Siemon Company. Mini-Com® and Panduit® are registered trademarks of Panduit Corp. SYSTIMAX® is a registered trademark of CommScope, Inc. TracJack®, Series II® & Ortronics® are registered trademarks of Ortronics/Legrand.