



Color :  Black

UPC Code : 078477629963

Country Of Origin : Mexico

NEMA :  5-20R

Available Colors :


Yellow

15W33-B

Wetguard Watertight Straight Blade Connector

20 Amp, 125 Volt, NEMA 5-20R, 2P, 3W, Connector, Straight Blade, Industrial Grade, Corrosion Resistant, Grounding, Wetguard- BLACK

ROHS Compliant : Yes

- **BATTLE THE ELEMENTS-** Resistant to water, acids, alkalis, and many automotive and industrial lubricants and solvents.
- **ADVANCED LID DESIGN-** Our spring-loaded flip lid is impact and chemical resistant with a Valox® PBT cover
- **MORE SECURE-** Dual-hasp provides additional lockout /tagout option for added security.
- **DURABLE-** Ideal for harsh environments with added resistance against heat, chemical corrosion, and physical abrasion

Technical Information

Electrical Specifications

Amperage : 20 A

Current Limiting : Full Rated Current

Dielectric Voltage :
Withstands 2000V per UL498

Grounding : Grounding

Pole : 2

Temperature Rise : Max 30C
after 250 cycles OL at 200
percent rated current

Voltage : 125 VAC

Wire : 3

Material Specifications

Assembly Screws : Stainless
Steel 300

Blades/Contacts : Nickel-
Plated Brass

Body Material : EPTR Rubber

Bushing : Santoprene TPV

**Compression Nut, Strain
Relief :** Nylon

Terminal Screws : Electroless
Nickel-coated Brass

Wire Module : Nylon

Environmental Specifications

Environment : Wet

Flammability : Rated V-2 per
UL 94

IP Rating : IP66, IP67, IP69K

Operating Temperature : -40°
C to 60°C

Mechanical Specifications

Cord Grip Range (in) : .234-.
687

Cord Range : .375 - .655

Terminal Accom. : 18-10 AWG

Terminal ID : Brass-Hot,
Green-Ground, Silver-Neutral

Product Features

Assembly Screws : Stainless Steel 300

Blades/Contacts : Nickel-Plated Brass

Body Material : EPTR Rubber

Brand : Wetguard

Color : Black

Device Type : Straight Blade Connector

NEMA : 5-20R

Standards and Certifications

ANSI : C-73

CSA C22.2 No. 42 : File LR-406


NEMA : WD-6

NOM : 057

UL : 498

Warranty : Limited Lifetime Warranty

Wiring Diagram



SPECIFICATION SUBMITTAL

JOB NAME: JOB NUMBER:	CATALOG NUMBERS: <table border="1" style="width: 100%; border-collapse: collapse;"><tr><td style="width: 50%; height: 20px;"></td><td style="width: 50%; height: 20px;"></td></tr><tr><td style="height: 20px;"></td><td style="height: 20px;"></td></tr></table>				

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)

5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.