


# W2125-R6



International Pin & Sleeve Receptacle

125 Amp, 200-250 Volt, 2P+E (2P, 3W), Clock Position 6, IEC/EN 60309-1 & 60309-2, International Configuration Panel Mounting Socket Outlet, Industrial Grade, IP66/67, Watertight - BLUE

**ROHS Compliant** : Yes

## Technical Information

### Electrical Specifications

**Amperage** : 125 A

**Frequency** : 50/60Hz

**Pole** : 2

**Voltage** : 200/250 VAC

**Wire** : 3

### Environmental Specifications

**IK Rating** : IK08

**IP Rating** : IP66/IP67

**Operating Temperature** : -25° C to 40°C

### Material Specifications

**Contacts** : Nickel Plated Brass

**Housing** : Halogen-free engineering polymer

### Mechanical Specifications

**Terminal Accom.** : #4 - 2/0 AWG

### Product Features

**Color** : Blue

**Configuration** : International

**Device Type** : Receptacle

### Standards and Certifications

**CE** : Marked

**IEC Rating** : 60309-1 and 60309-2

**NOM Certified** : Yes

**RETIE Certified** : Yes

**UPC Code** : 078477678749

**Country Of Origin** : Italy

## SPECIFICATION SUBMITTAL

|                                                                                             |                                                                                                                                                                                                          |                      |                      |                      |                      |
|---------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|----------------------|----------------------|----------------------|
| <p><b>JOB NAME:</b></p> <input type="text"/> <p><b>JOB NUMBER:</b></p> <input type="text"/> | <p><b>CATALOG NUMBERS:</b></p> <table border="1"> <tr> <td><input type="text"/></td> <td><input type="text"/></td> </tr> <tr> <td><input type="text"/></td> <td><input type="text"/></td> </tr> </table> | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| <input type="text"/>                                                                        | <input type="text"/>                                                                                                                                                                                     |                      |                      |                      |                      |
| <input type="text"/>                                                                        | <input type="text"/>                                                                                                                                                                                     |                      |                      |                      |                      |

### Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

### Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52) 5386- 1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

**Visit our Website at: [www.leviton.com](http://www.leviton.com)**

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:  
[www.leviton.com/international/contacts](http://www.leviton.com/international/contacts)

**© 2024 Leviton Manufacturing Co., Inc.**