



Shown actual size: Maestro Wireless dimmer and 1-gang Claro wallplate in White (WH).

Shown actual size: Pico wireless remote in White (WH), W: 1.25 in (31.75 mm) x H: 2.63 in (66.68 mm) x D: .33 in (8 mm). For details, see p. 178)

Product family features

- Uses Lutron Clear Connect® radio frequency (RF) technology, which provides reliable RF communication with Pico® wireless remotes (see p. 178) and Radio Powr Savr™ wireless sensors (see pp. 198 and 202)
- Combine up to 10 wireless devices (dimmers, switches, sensors and/or wireless remotes)
- True multi-location dimming from every location
- Tap on to favorite level; tap off; tap twice for full on
- Touch rocker to adjust light level
- Delayed off provides light as you exit the room
- **C•L® model available**
- Communicates at 434 MHz frequency
- Coordinating Claro®, Satin Colors®, and Stainless Steel wallplates only available separately
- Custom engraving available for wallplates, see p.237

Control types

- Single-pole (one location)
- Multi-location (up to 10 locations)
- Wireless multi-location (up to 10 locations)

Direct load type compatibility

- Incandescent/halogen lighting
- Dimmable CFL/LED lighting (screw-base)
- Magnetic low-voltage lighting
- Electronic low-voltage lighting
- Fluorescent lighting
- LED lighting
- Switched lighting/fan/motor

Load type requiring load interface

- Neon/cold cathode lighting

Lighting load interfaces may be applicable for some load type, voltage, and capacity combinations. For additional information, see pp.255–259.

Available finishes

Use **BOLD** color code in model number (Example: MRF2-600M-**PD**)

Gloss finishes*



WH
White

LA
Light Almond

AL
Almond

IV
Ivory

GR
Gray

BR
Brown

BL
Black

Satin Colors® finishes*



SW
Snow

LS
Limestone

BI
Biscuit

ES
Eggshell

PD
Palladium

TP
Taupe

ST
Stone



BG
Bluestone

PL
Plum

SG
Sea Glass

TQ
Turquoise

GS
Goldstone

DS
Desert Stone

GB
Greenbriar



MS
Mocha Stone

TC
Terracotta

SI
Sienna

HT
Hot

MR
Merlot

MN
Midnight

SS
Stainless Steel

Metal finish wallplate**

* Coordinating wallplates only available separately. For wallplate information, see p. 236.

** Stainless Steel wallplate only available separately and includes black plastic trim/adaptor, visible from side. Match with separate Black (BL) or Midnight (MN) controls. For wallplate information, see p. 236.

Digital fade wireless dimmers



- Tap on to preset level; tap off
- Tap twice for full on
- Press, hold, and release for delayed fade-to-off
- Touch rocker to adjust light level
- Provides true dimming from each location with companion dimmers or Pico® wireless remotes (see p. 151)
- C•L® dimmer offers reliable dimming of dimmable CFLs/LEDs, as well as halogens and incandescents



Incandescent/halogen dimmer



Dimmable CFL/LED (screw-base) dimmer

Digital fade wireless C•L® dimmer*

Multi-location/single-pole MRF2-6CL-**XX**¹
120V 600W (Inc) 150W (CFL/LED)

Visit **www.lutron.com/dimcflled** for an approved list of dimmable CFL/LED bulbs, and how to calculate wattage when mixing lamp types.

Adjustable low-end trim.



Incandescent/halogen dimmers

Digital fade wireless dimmer*

Multi-location/single-pole MRF2-600M-**XX**¹
120V 600W

Digital fade wireless dimmer*, Pico® wireless remote and wallplate

Multi-location/single-pole MRF2-600MTHW-WH
120V 600W



Incandescent/halogen dimmer



Magnetic low-voltage dimmer

Digital fade wireless dimmer*

Multi-location/single-pole MRF2-6MLV-**XX**¹
120V 600W (Inc)
600VA/450W (MLV)

Digital fade wireless dimmer—
specification grade*

Multi-location/single-pole MRF2-10D-120-**XX**¹
120V 1000W (Inc)
1000VA/800W (MLV)

The stated W (Watt) rating is the maximum incandescent lamp load. Ratings for MLV loads represent the maximum of the total lamp wattage plus MLV transformer loss (typically 20%).

XX¹: Gloss and Satin Colors® codes, see p. 153
Wallplates not included. Order separately, see p. 236

All models must be derated if ganged unless otherwise noted, see pp. 250–252 and 254.

* Minimum load required, see specification submittal