

Energi TriPak® components

1a Is control of overhead lighting required?

Wireless switches



Maestro Wireless® switch dimensions

W: 2.94" (75 mm)

H: 4.69" (119 mm)

D: 1.44" (38 mm)



5 A 2-button switch dimensions

W: 2.94" (75 mm)

H: 4.69" (119 mm)

D: 1.44" (38 mm)

Select one switch per lighting zone

- Select appropriate model based on the size of the connected load
 - 5 A: 600 W lighting @ 120 V or 1385 W @ 277 V
 - 6 A: 600 W lighting @ 120 V
 - 8 A: 960 W lighting @ 120 V or 2216 W @ 277 V
- If existing switch does not have a neutral, choose the model available for 120/277 V with no neutral required
- Select from up to 27 colors to complement the décor*
- Add an additional Pico® remote in step 6 for rooms with multiple switches for a single zone

Maestro Wireless switch

MRF2-8S-DV-XX – 8 A lighting, 1/10 HP fan @ 120 V only, 120-277 V, no neutral

MRF2-6ANS-XX – 6 A lighting, 1/10 HP fan, 120 V only

MRF2-8ANS-120-XX – 8 A lighting, 1/4 HP fan, 120 V only

5 A 2-button switch

PD-5S-DV-XX – 5 A lighting, 120/277 V, no neutral

* 5 A 2-button switch only available in white, ivory, light almond, black

Ordering information

Model number Description



Maestro Wireless® switches and 5 A 2-button RF switch*

PD-5S-DV-XX	5 A lighting, 3 A fan (1/10 HP motor, 120 V only) 120/277 V, no neutral
MRF2-6ANS-XX	6 A lighting, 3 A fan (1/10 HP motor), 120 V
MRF2-8ANS-120-XX	8 A lighting, 5.8 A fan (1/4 HP motor), spec grade, 120 V
MRF2-8S-DV-XX	8 A lighting, 3 A fan (1/10 HP motor, 120 V only), spec grade



Maestro Wireless dimmers*

MRF2-6CL-XX	150 W dimmable CFL/LED, 600 W incandescent/halogen, 120 V
MRF2-600M-XX	600 W incandescent/halogen, 120 V
MRF2-6MLV-XX	600 W/600 VA incandescent/halogen/MLV, 120 V
MRF2-6ND-120-XX	600 W/600 VA incandescent/halogen/MLV, neutral wire, 120 V
MRF2-10D-120-XX	1000 W/1000 VA incandescent/halogen/MLV, spec grade, 120 V
MRF2-F6AN-DV-XX	6 A lighting, 3-wire fluorescent, spec grade, 120–277 V
MRF2-6ELV-120-XX	600 W ELV, 120 V



Maestro Wireless tabletop lamp dimmer*

MRF2-3LD-XX	300 W lamp dimmer, incandescent/halogen, 120 V
-------------	--

Stairwell fixtures**



FXSWXX14SL232U51SMXXWH	4 ft, 2 lamp, T8 fluorescent, 50% high-end, 10% low-end, 120/277 V
FXSWXX14SL232U82SMXXWH	4 ft, 2 lamp, T8 fluorescent, 80% high-end, 20% low-end, 120/277 V
FXSWXX14SLLC1U51SMXXWH	4 ft, 17 W, 1500 lumens, 4000 K LED, 50% high-end, 10% low-end, 120/277 V
FXSWXX14SLLC1U82SMXXWH	4 ft, 17 W, 1500 lumens, 4000 K LED, 80% high-end, 20% low-end, 120/277 V



PowPak relay module

RMJ-5R-DV-B	5 A switch
RMJ-5RCCO1-DV-B	5 A switch with one contact closure output
RMJ-16R-DV-B	16 A switch
RMJ-16RCCO1-DV-B	16 A switch with one contact closure output
RMJ-H20R-DV-B	20 A general purpose switch



Model number	Description
L-PED3-XX	Pico wireless remote triple pedestal
L-PED4-XX	Pico wireless remote quadruple pedestal
PICO-WBX-ADAPT	Pico wireless remote wallbox adapter

Lamp Socket Wiring Tester

FDB-LSWT-T5/T8	600V, 100KHz, 0.125A max, CAT III
----------------	-----------------------------------

Maestro Wireless/Maestro® occupancy sensing control companion devices[†]

MA-AS-XX	Multi-location companion switch, 120V
MA-AS-277-XX	Multi-location companion switch, 277V
MA-R-XX	Multi-location companion dimmer, 120V
MA-R-277-XX	Multi-location companion dimmer, 277V



Wallplates

CW-1-XX	Claro 1-gang wallplate
CW-2-XX	Claro 2-gang wallplate
CW-3-XX	Claro 3-gang wallplate
CW-4-XX	Claro 4-gang wallplate

Gloss colors:

- S White (WH)
- S Ivory (IV)
- S Almond (AL)
- S Light Almond (LA)
- S Gray (GR)
- S Brown (BR)
- S Black (BL)

Satin Colors®:

- Hot (HT)
- Merlot (MR)
- Plum (PL)
- Turquoise (TQ)
- Sea Glass (SG)
- Midnight (MN)
- Sienna (SI)
- Terracotta (TC)
- Greenbriar (GB)
- Bluestone (BG)
- Taupe (TP)
- Eggshell (ES)
- Biscuit (BI)
- Snow (SW)
- Palladium (PD)
- Mocha Stone (MS)
- Goldstone (GS)
- Desert Stone (DS)
- Stone (ST)
- Limestone (LS)

Availability

- S = Stock items,
ship in 2 days
- = Satin Colors,
ship in 2–10 days