

LED OMNIDIRECTIONAL A-LAMP ENCLOSED RATED A19 GU24 JA8 SERIES



PRODUCT DESCRIPTION:

Designed to meet Title 24 code for the State of California, these JA8 LED A-lamps deliver even lighting equivalent to that of a 60W incandescent bulb, while consuming nearly 83 percent less energy. Open and enclosed rated models are available in two color temperatures.

FEATURES:

- Wattage: 9W, replacement for 60W Inc.
- Lumens: 800
- Supports T24 Part 6 high efficacy lighting requirements
- T20 Listed
- CRI: ≥ 92
- R9: ≥ 50
- Beam Angle: 300°
- Min. Dimming: $\leq 10\%$
- Saves more than 83% on energy
- Tc Max = 100°C
- Suitable for use in damp locations
- Suitable for use in fully enclosed luminaires
- 25,000 hour life (L70 standards)

APPLICATIONS:

- Pendants
- Table and floor lamps
- Sconces

WARRANTY:

1-year standard warranty
(further details available at www.maxlite.com/warranties)

MODEL SELECTION (Full list of order codes on pg. 2)

Typical order example: E9A19GUD927/JA8

E9A19	GUD	
FAMILY	BASE & DIMMABILITY	CRI & CCT
E9A19= 10 watts, Enclosed Rated A19	GUD= GU24, Dimmable	927/G2/JA8= 92 CRI, 2700K 930/G2/JA8= 93 CRI, 3000K

COMPATIBLE DIMMER LIST:

MANUFACTURE	DIMMER MODEL
AH	SDM/600
	SDM3/1000
ALMOND	LUXDM600-12
CTL	DM600-12-3
GE	18024
LEVITON	6631
	6672
	6683
	603-6631-A

MANUFACTURE	DIMMER MODEL
LEVITON	6631-A
	6631-LA
	6683-10Z
	IPI06-1LZ
	IPI10-1LZ
LUTRON	IPL06
	AYCL-153P-WH
	AYCL-153PH
	DVCL-153P-WH

MANUFACTURE	DIMMER MODEL
LUTRON	DVWCL-153PH-WHC
	S-603PH-WH
	SCL-153PH-WH
	TGCL-153PH-WH
MAAXIMA	MEW-DM600

SPECIFICATIONS:

		E9A19GUD9xx/JA8
ITEM	SPECIFICATION	ENCLOSED RATED
GENERAL PERFORMANCE	Power Consumption	9W
	Lumens Delivered	800
	Efficacy (lm/w)	80
	CRI	≥92
	R9	≥50
	Color Temperature (CCT)	2700K, 3000K
	Lumen Maintenance (L70)	25,000 Hours
ELECTRICAL	Power Factor	≥0.90
	Input Voltage	120V
PHYSICAL	Base Type	GU24
	Operating Temperature	-4°F - 104°F
CERTIFICATION	Environment	Dry, Damp, Enclosed
	Warranty	1 year standard warranty

ORDERING:

ORDER CODE	MODEL	CCT	WATTS	EQUIVALENCY	OUTPUT (LUMENS)	EFFICACY (lm/W)	CRI	DIMENSIONS (D" x MOL")
ENCLOSED RATED - GU24 BASE MODEL								
102490	E9A19GUD927/JA8	2700K	9W	60W Inc.	800	80	92	2.36" x 4.21"
102491	E9A19GUD930/JA8	3000K					93	