

9W SINGLE-ENDED T8 TUBES

UL TYPE-B SERIES



PRODUCT DESCRIPTION:

MaxLite LED T8 Linear Replacement Lamps are the ideal energy saving choices when upgrading traditional linear T8 or T12 fluorescent lamps in fixtures containing standard G13 (medium bi-pin) sockets. The LED T8 lamps are designed to provide appropriate light levels while utilizing a dedicated internal driver and require non-shunted G13 medium bi-pin lamp holders.



FEATURES:

- 9.2 Watts, 1600-1650 lumens
- Shatterproof PET coated glass
- Universal Voltage: 120V-277V Applications
- Requires Non-Shunted Sockets
- Suitable for enclosed fixture
- Suitable for dry and damp locations

WARRANTY:

5-year standard warranty (further details available at www.maxlite.com/warranties) Product may be eligible for a warranty extension to 10 years, for an additional fee. Contact

ORDER STRUCTURE

WATTAGE & FAMILY	SIZE	COLOR TEMPERATURE	LENS
L9T8SE= 9W, Single-Ended T8	4= 4ft	35= 3500K 40= 4000K 50= 5000K	-CG= Coated Glass, Frosted

STOCKED ITEMS:

ORDER CODE	MODEL NUMBER	PRODUCT ID
105011	L9T8SE435-CG	PLJDNC300MMB
105012	L9T8SE440-CG	PL649BZBPEK2
105013	L9T8SE450-CG	PLIT48RC93TS

SPECIFICATIONS:

ITEM	L9T8SE4xx-CG
NOMINAL WATTAGE (W)	9W
LUMENS (LM)	1600-1625 lm
EQUIVALENCY	32W
EFFICACY (LM/W)	174-177 lm/w
BEAM ANGLE	280°
CRI	≥80
CCT (K)	3500K, 4000K, 5000K
L70 LIFETIME (HRS)	50,000 Hrs
VOLTAGE	120-277V
POWER FACTOR	≥0.90
OPERATING TEMPERATURE	-4°F to 113°F (-20°C to 45°C)
LISTINGS	cULus, FCC, Flicker Free
ENVIRONMENT	Dry/Damp Location
DESIGNLIGHT CONSORTIUM	DLC Standard