

|             |     |      |         |
|-------------|-----|------|---------|
| Version     | 2.0 | Date | 8/22/23 |
| Prepared By | JC  |      |         |


| PRODUCT SPECIFICATION |                         |                                                                                     |  |
|-----------------------|-------------------------|-------------------------------------------------------------------------------------|--|
| Category              | Filament HID            |                                                                                     |  |
| Item Number           | 4626                    |                                                                                     |  |
| Stock Code            | LED30FHID/ED28/EX39/830 |                                                                                     |  |
| Mounting              | EX39                    |                                                                                     |  |
| Lamp Shape            | ED28                    |                                                                                     |  |
| PICTURE               |                         |  |  |

| ELECTRICAL CHARACTERISTICS |         |                            |      |
|----------------------------|---------|----------------------------|------|
| Rated Wattage (W)          | 30      | Replacement<br>Wattage (W) | 150W |
| Tested Wattage (W)         | 30      |                            |      |
| Input Voltage (V)          | 120-277 |                            |      |
| Voltage Frequency (Hz)     | 50/60   | Surge Protect Level        | 2KV  |
| Input Current (A)          | 0.3     | Dimmable                   | -    |
| Power Factor               | >0.9    | AUX (12V) Line             | -    |
| THD                        | <20%    |                            |      |

| PHOTOMETRIC CHARACTERISTICS |       |                |       |
|-----------------------------|-------|----------------|-------|
| Lumen (lm)                  | 6,000 | CCT (K)        | 3000K |
| Efficacy (lm/w)             | 200   | Beam Angle (°) | 360°  |
| CRI                         | >80   |                |       |

| GENERAL CHARACTERISTICS    |             |
|----------------------------|-------------|
| Operating Temperature (°F) | -4°F ~ 113° |
| Storage Temperature (°F)   | -4°F ~ 122° |
| IP Rating                  | -           |
| IK Rating                  | -           |
| Rated Life (Hrs)           | 35,000      |
| Warranty (Yrs)             | 5           |

| ACCESSORIES |            |             |
|-------------|------------|-------------|
| Item #      | Stock Code | Description |
|             |            |             |
|             |            |             |
|             |            |             |
|             |            |             |
|             |            |             |

| PRODUCT DIMENSIONS   |       |     |                                                                                      |
|----------------------|-------|-----|--------------------------------------------------------------------------------------|
| Diameter- in / (mm)  | 3.54" | 90  |  |
| MOL- in / (mm)       | 9.25" | 235 |                                                                                      |
| Depth- in / (mm)     | -     | -   |                                                                                      |
| IK Rating            | -     | -   |                                                                                      |
| Weight (lbs)         | 0.44  |     |                                                                                      |
| Mounting Height (ft) | -     |     |                                                                                      |
| Cable Length (ft)    | -     |     |                                                                                      |

| CERTIFICATIONS     |          |      |   |
|--------------------|----------|------|---|
| UL/ETL             | ETL/cETL | CEC  |   |
| NSF/ETL Sanitation |          | JA8  |   |
| Energy Star        |          | FCC  | ✓ |
| DLC                |          | RoHs | ✓ |

| DOCUMENTS |   |             |  |
|-----------|---|-------------|--|
| LM79      |   | IES File    |  |
| LM80      |   | Dimmer List |  |
| DOE       | ✓ |             |  |
|           |   |             |  |

| COMMENTS |
|----------|
|          |