

NFBIC-4INCAT

4" Recessed Line Voltage Fire Rated Housing - Two Hour Fire & Sound Dampening Rated

Source: 35W max.

(Lamp type varies per trim)

PRODUCT DESCRIPTION

Specification grade fire-rated new construction housing. The double wall fixture incorporates a non-combustible fiber insulation to prevent passage of flames, toxic gases, ignitable gasses into ceiling plenums. The cULus listed housing is rated for a minimum of two hours protection. The noncombustible fiber fill also acts as sound deadening material eliminating the transfer of sound between floors. Suitable for commercial, multi-family and residential applications.

FEATURES

- Rated for direct contact with insulation
- cULus classified Two Hour Fire Rating
- cULus listed for damp location and through branch circuit wiring
- 24-1/2" Bar hangers with captive nails & alignment feet
- Accommodates 1-3/4" maximum ceiling thickness

CONSTRUCTION

Plaster Frame: High quality 0.03" steel die cut one piece frame.

Housing: Die formed 20 gauge galvanized steel construction. Housing interior is comprised of a flexible non-combustible insulation.

Air Flow Restriction: Housing has factory installed gaskets to restrict airflow from room into ceiling plenum to <2CFM (cubic feet per minute) in accordance with ASTM-283 Air-Tight requirements.

Junction Box: Prewired 0.03" thick galvanized steel, contains one 1-1/8", one 1/2", three 7/8" knockouts and four Romex pryouts with strain relief and snap on covers. All leads are #18AWG wire, the ground wire is connected to the bottom, and quick connectors are supplied on all leads. Through branch circuit wiring, (4-in, 4-out).

Quick Connect Feature: Housing contains three UL approved quick connections that allow insertion of 1/4" stripped solid or tinned standard conductors to be inserted into the connector. Connectors are pre-attached to fixture power, common, and ground circuits.

Bar Hangers: Two 13-3/4" to 24-1/2" adjustable bar hangers with captive nails are included on frame. Bar hangers are parallel to junction box, but can be repositioned 90° perpendicular to junction box if desired. "L" Shaped bar hanger foot to align to bottom of construction joist. A T-Bar notch allow for easy installation in a suspended ceiling.

Installation: Classified for use in two hour fire rated L500 Series floor-ceiling designs in the UL Fire Resistance Directory. Mark Spacing, number of luminaires not to exceed the ratio, one per 25sq ft of the total ceiling area, with minimum separation of 3ft between luminaires. Access above ceiling required.

ELECTRICAL

Voltage: 120V

Socket: Medium base

Wattage: 35W max.

Lamp Type: Varies per trim

Dimming: Varier per lamp

Thermal Protection: Standard UL thermal protector rated for 110°C is affixed to inner top surface of housing.

Sound Deadening: STC tested by a certified acoustical testing lab. STC (Sound Transfer Class) will only change by 1 point when NFBIC housing is installed.

COMPATIBLE TRIMS

CATALOG NO.	DESCRIPTION
NS-12	4" Round Adjustable Gimbal
NS-18	4" Round Adjustable Eyeball
NS-40	4" Baffle
NS-40P	4" Phenolic Baffle
NS-41	4" Black Baffle
NS-41P	4" Black Phenolic Baffle
NS-42	4" Gold Reflector
NS-43	4" Black Reflector
NS-44	4" Clear Reflector
NS-44HZ	4" Haze Reflector
NS-46	4" White Reflector
NS-52	4" Natural Metal Reflector
NS-53	4" Copper Reflector
NS-53BZ	4" Bronze Reflector
NS-76	4" Round Lensless Baffle Shower Trim

LABELS AND LISTINGS

- cULus Classified for Two Hour Fire Rating
- cULus Listed for Damp Location w/ Feed Through (Wet Location when used with designated trims)
- Meets or exceeds ASTM-283 Air-Tight requirements
- ANSI/UL 263
- ANSI/UL 1598
- STC tested for sound transfer





Type

Project

Catalog No.

Notes

PRODUCT IMAGES & DIMENSIONS



4" Recessed Line Voltage Fire Rated Housing

Catalog No.

NFBIC-4INCAT = 4" Recessed Line Voltage Fire Rated Housing

Example: NFBIC-4INCAT = 4" Recessed Line Voltage Fire Rated Housing