

NIO-4SND SQ

4" Iolite Square Reflector with Square Aperture

Source: 14W to 28W LED
800lm to 2500lm

PRODUCT DESCRIPTION

4" Iolite reflectors can be specified for use with Iolite new construction or remodel housings. Deep regressed cone reflectors optimize visual cut-off.

FEATURES

- 800lm, 1000lm, 1500lm, 2000lm or 2500lm LED packages
- 2700K, 3000K, 3500K, 4000K, 5000K @ 90+ CRI
- Cree® LED COB or Comfort Dim Technology
- Flood optic, narrow flood and spot optics (included)
- 5-Year limited warranty

SPECIFICATION

Construction: Reflectors are constructed of heat dissipating, die-cast aluminum. The aluminum die-cast LED heat sink is threaded to fit the reflector and transfer heat.

Mounting: Reflector includes friction blades to mount securely to housing.

OPTICS

800-1000lm: Each reflector includes field changeable optics (25° spot, 38° narrow flood and 56° flood - preinstalled). Premium 15° and 25° TIR optics are also available.

1500-2500lm: Each reflector includes field changeable TIR optics (30° spot, 45° narrow flood - preinstalled and 65° flood).

ELECTRICAL

Lumens / Wattage: 800lm / 14W, 1000lm / 14W, 1500lm / 20W, 2000lm / 24W, 2500lm / 28W

Color Temperature: 2700K, 3000K, 3500K, 4000K, 5000K

CRI: 90+ CRI

Operating Temp.: Specified by housing

Lifetime: 50,000 hours @ L70

Comfort Dim: Comfort Dim color tunes the temperature from a bright 3100K, to a romantic and comfortable 2000K on a gradual, even curve. Available in 800lm only.

Dimming: Specified by housing

COMPATIBLE HOUSINGS

Reflectors are compatible with respective Iolite housings manufactured by Nora Lighting.

CATALOG NO.	DESCRIPTION	LUMENS / WATTAGE
NHIOICD-48	ICAT New Construction	800-1000lm / 14W
NHIOICDCP-48	Chicago Plenum	800-1000lm / 14W
NHRIIC-48	ICAT Remodel	800-1000lm / 14W
NHIOICD-415	ICAT New Construction	1500lm / 20W
NHIOICDCP-415	Chicago Plenum	1500lm / 20W
NHIOICD-420	ICAT New Construction	2000lm / 24W
NHIOICDCP-420	Chicago Plenum	2000lm / 24W
NHIOICD-425	ICAT New Construction	2500lm / 28W
NHIOICDCP-425	Chicago Plenum	2500lm / 28W

Accessories: Reflectors will accommodate (1) hex louver and (1) translucent deco collar or opaque snoot, no accessory holder is required, see accessories page. Flush mount mud ring is available to give the appearance of a trimless reflector, compatible with new construction housing only.

LABELS AND LISTINGS

- cULus Listed for Wet Locations
- ENERGY STAR certified
- [5-Year Limited Warranty](#)
- RoHS Compliant
- Certified to the high efficacy requirements of California Title 24 JA8-2019




Type

Project

Catalog No.


Notes

PRODUCT IMAGES & DIMENSIONS



NIO-4SND SQ

Square Reflector with Square Aperture
Non-Adjustable




BB

Black Reflector
Black Flange




BW

Black Reflector
White Flange




BZ

Bronze Reflector
Bronze Flange




CHMPW

Champagne Haze Reflector
Matte Powder White Flange



HN

Haze Reflector
Natural Metal Flange



HW

Haze Reflector
White Flange



HZMPW

Haze Reflector
Matte Powder White Flange



MPW

Matte Powder White Reflector
Matte Powder White Flange



WW

White Reflector
White Flange

4" Iolite Square Reflector with Square Aperture - Dedicated Housing Required

Reflector Type	Color Temp.	Finish	Lumens / Wattage
NIO-4SND SQ = Square Reflector with Square Aperture	27X = 2700K	BB = Black / Black	(blank) = 800lm / 14W
	30X = 3000K	BW = Black / White	/10 = 1000lm / 14W
	35X = 3500K	BZ = Bronze / Bronze	/HL = 1500-2500lm
	40X = 4000K	CHMPW = Champagne / Matte Powder White	(varies by housing)
	50X = 5000K	HN = Haze / Natural Metal	
	CDX = Comfort Dim [†]	HW = Haze / White	
		HZMPW = Haze / Matte Powder White	
		MPW = Matte Powder White	
		WW = White / White	

[†] Comfort Dim technology available in 800lm & uses non-Cree COB modules. 1" & 2" Iolite uses a different dimming curve than 4" Comfort Dim

Compatible Housings

Housing Type
NHIOICD-48 = ICAT New Construction / 800-1000lm / 14W
NHIOICDCP-48 = Chicago Plenum / 800-1000lm / 14W
NHRIIC-48 = ICAT Remodel / 800-1000lm / 14W
NHIOICD-415 = ICAT New Construction / 1500lm / 20W
NHIOICDCP-415 = Chicago Plenum / 1500lm / 20W
NHIOICD-420 = ICAT New Construction / 2000lm / 24W
NHIOICDCP-420 = Chicago Plenum / 2000lm / 24W
NHIOICD-425 = ICAT New Construction / 2500lm / 28W
NHIOICDCP-425 = Chicago Plenum / 2500lm / 28W

Example: NIO-4SND SQ27XWW = 4" Iolite Square Reflector with Square Aperture, 2700K, White finish, 800lm / 14W

4" Iolite Accessories

4" Iolite Square Reflector with Square Aperture

Type

Project


Catalog No.

Notes

FIELD CHANGEABLE OPTICS

Iolite reflectors include spot, narrow flood and flood optics. Optics can be changed in the field by removing LED module from die-cast reflector. Replacement optics include an optional frosted lens.

Note: Frosted filter-optics and Premium TIR optics are not compatible with /HL LED modules.



Frosted Filter-Optic

NIO-REFL15FR
NIO-REFL25FR
NIO-REFL38FR
NIO-REFL60FR

15° Optic
25° Optic
38° Optic
56° Optic

Optic assembly includes optional frosted lens. 25°, 38° and 56° optics are included with 800lm and 1000lm reflector.
Not compatible with /HL LED module.



Premium TIR Optics


NIO-REFLTIR15
NIO-REFLTIR25

15° Optic
25° Optic

Not compatible with /HL LED module or Comfort Dim (CDX) technology

ACCESSORIES

Iolite accessories can be added at any point in the design process. Accessories easily install between LED module and die-cast reflector. Luminaire will accommodate (1) hex louver and (1) collar accessory, no accessory holder required.



Translucent Decorative Collar

NIO-AS14(color) 5/8" length
NIO-AS19(color) 3/4" length
NIO-AS26(color) 1" length
Color:
AM (amber), BLU (blue), FR (frosted), R (red)

Translucent collars color the aperture with the specified color while producing white general light. Collars are available in different lengths. Use to add interest, create a theme, match a theme or define a space.



Opaque Collar Snoot

NIO-AS14(color) 5/8" length
NIO-AS19(color) 3/4" length
NIO-AS26(color) 1" length
Color:
BLK (black), MPW (matte powder white), WH (white)

Opaque snoot greatly reduces aperture brightness while preserving light output. (Note: Black snoot will reduce light)




Hex Cell Louver

NIO-HC Black
Hex cell louver subtly reduces aperture brightness by reducing light output by about 20%.

FLUSH MOUNT

4" Iolite reflectors can be installed flush with the drywall for a flush mount appearance. A flush mount mud ring is installed after the drywall and a professional drywall finisher floats the ceiling to blend in the mud ring.



Flush Mount Mud Ring

NIO-FMMR-4S

Square Mud Ring

Mounts reflector flush to ceiling with flange visible. Mud ring attaches to drywall. **Only for use with NH10ICD-48 or NH10ICDCP-48 new construction housings and NIO-4S reflectors.**
Dimensions: 7-7/8" diameter 1/2" thick

PHOTOMETRICS

4" Iolite Square Reflector with Square Aperture
800 lumens

Type


Project

Catalog No.

Notes

Test Information

Test Number: NTR11370
Part Number: NIO-4SNDQ27XHW
Beam Spread: 27° Spot
Lumens: 931lm
Wattage: 13.86W
Efficacy: 67lpw
CCT / CRI: 2700K / 90 CRI
Spacing Criteria (0°-180): 0.42
Spacing Criteria (90°-270): 0.14



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	158fc	1'-11"
6'	70.1fc	2'-11"
8'	39.5fc	3'-11"
10'	25.3fc	4'-10"
12'	17.5fc	5'-10"

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	742	79.7
0-40	878	94.4
0-60	920	98.8
0-90	926	99.5
90-180	5	0.5
0-180	931	100

Candela Table

Vertical Angles	Candela
0	2525
5	2206
15	956
25	454
35	59
45	31

Test Information

Test Number: NTR11371
Part Number: NIO-4SNDQ27XHW
Beam Spread: 38° Narrow Flood
Lumens: 933lm
Wattage: 13.85W
Efficacy: 67lpw
CCT / CRI: 2700K / 90 CRI
Spacing Criteria (0°-180): 0.64
Spacing Criteria (90°-270): 0.16



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	111fc	2'-10"
6'	49.3fc	4'-1"
8'	27.8fc	5'-6"
10'	17.8fc	6'-11"
12'	12.3fc	8'-4"

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	745	79.9
0-40	882	94.5
0-60	922	98.8
0-90	928	99.5
90-180	4	0.5
0-180	933	100

Candela Table

Vertical Angles	Candela
0	1776
5	1708
15	1236
25	526
35	97
45	32

Test Information

Test Number: NTR11372
Part Number: NIO-4SNDQ27XHW
Beam Spread: 56° Flood
Lumens: 888lm
Wattage: 13.85W
Efficacy: 64lpw
CCT / CRI: 2700K / 90 CRI
Spacing Criteria (0°-180): 0.84
Spacing Criteria (90°-270): 0.14



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	68.2fc	4'-2"
6'	30.3fc	6'-5"
8'	17fc	8'-6"
10'	10.6fc	10'-7"
12'	12.7fc	12'-8"

Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	641	72.2
0-40	824	92.8
0-60	877	98.7
0-90	884	99.5
90-180	4	0.5
0-180	888	100

Candela Table

Vertical Angles	Candela
0	1090
5	1057
15	896
25	623
35	185
45	43

Lumen Output Multipliers

Color Temperature: 2700K (1.00), 3000K (1.03), 3500K (1.07), 4000K (1.2), 5000K (1.21)

PHOTOMETRICS

4" Iolite Square Reflector with Square Aperture
1000 lumens

Type


Project

Catalog No.

Notes

Test Information

Test Number: NTR11261
Part Number: NIO-4SNDQ27XHW/10
Beam Spread: 25° Spot
Lumens: 1181lm
Wattage: 14.2W
Efficacy: 83lpw
CCT / CRI: 2700K / 90 CRI
Spacing Criteria (0°-180): 0.5
Spacing Criteria (90°-270): 0.42



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	182fc	1'-11"
6'	80.7fc	2'-11"
8'	45.4fc	3'-11"
10'	29.1fc	4'-11"
12'	20.2fc	5'-10"

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	943	79.8
0-40	1101	93.3
0-60	1166	98.7
0-90	1173	99.3
90-180	8	0.7
0-180	1181	100

Candela Table

Vertical Angles	Candela
0	2906
5	3065
15	1407
25	628
35	97
45	43

Test Information

Test Number: NTR11262
Part Number: NIO-4SNDQ27XHW/10
Beam Spread: 37° Narrow Flood
Lumens: 1184lm
Wattage: 14.33W
Efficacy: 83lpw
CCT / CRI: 2700K / 90 CRI
Spacing Criteria (0°-180): 0.64
Spacing Criteria (90°-270): 0.62



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	143fc	2'-8"
6'	63.5fc	4'-1"
8'	35.7fc	5'-5"
10'	22.9fc	6'-10"
12'	15.9fc	8'-2"

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	951	80.3
0-40	1113	94
0-60	1168	98.7
0-90	1176	99.3
90-180	8	0.7
0-180	1184	100

Candela Table

Vertical Angles	Candela
0	2288
5	2247
15	1524
25	681
35	101
45	40

Test Information

Test Number: NTR113263
Part Number: NIO-4SNDQ27XHW/10
Beam Spread: 55° Flood
Lumens: 1182lm
Wattage: 14.45W
Efficacy: 82lpw
CCT / CRI: 2700K / 90 CRI
Spacing Criteria (0°-180): 0.82
Spacing Criteria (90°-270): 0.82



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	92.4fc	4'-2"
6'	41.1fc	6'-4"
8'	23.1fc	8'-4"
10'	14.8fc	10'-5"
12'	10.3fc	12'-6"

Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	866	73.2
0-40	1098	92.9
0-60	1165	98.6
0-90	1174	99.3
90-180	8	0.7
0-180	1182	100

Candela Table

Vertical Angles	Candela
0	1478
5	1457
15	1209
25	834
35	229
45	55

Lumen Output Multipliers

Color Temperature: 2700K (1.00), 3000K (1.02), 3500K (1.11), 4000K (1.21), 5000K (1.18)