

NL-3325

3" Frosted Dome Lens with Reflector

FEATURES

Trim: Precision spun 0.050 aluminum high grade reflector that includes a frosted dome lens. Gimbal ring allows lamp to be mounted on top of the trim and adjustable up to 35°.

Mounting: Trim includes three trim clips that securely mount trim in housing.

COMPATIBLE HOUSINGS

Compatible with Line Voltage and Low Voltage housings. See individual specification sheets for more information.

LAMP

Line Voltage

50W 120V MR16 GU10 Max. (NH-350AT; NHIC-350AT; NHR-354AT)

Low Voltage

Important: Do not use glass lens (provided) when already using lamp with glass cover

50W 12V MR16 (NL-301 Series; NLIC-301 Series; NLR-304 Series; NLR-305 Series)

LABELS AND LISTINGS

cULus Listed for Wet Location when used with compatible housing.



Type

Project

Catalog No.

Notes

Product Images and Dimensions



NL-3325B
Black Ring



NL-3325BZ
Bronze Ring



NL-3325CO
Copper Ring




NL-3325G
Gold Ring



NL-3325N
Natural Metal Ring



NL-3325W
White Ring



3" Frosted Dome Lens with Reflector

Catalog No.

NL-3325B = Frosted Dome Lens with Specular Clear Reflector and Black Metal Ring

NL-3325BZ = Frosted Dome Lens with Specular Clear Reflector and Bronze Metal Ring

NL-3325CO = Frosted Dome Lens with Specular Clear Reflector and Copper Metal Ring

NL-3325G = Frosted Dome Lens with Specular Clear Reflector and Gold Metal Ring

NL-3325N = Frosted Dome Lens with Specular Clear Reflector and Natural Metal Ring

NL-3325W = Frosted Dome Lens with Specular Clear Reflector and White Metal Ring

Compatible Housings

Line Voltage

Catalog No.

NH-350AT = 3" Non-IC Air-Tight New Construction Housing / 50W max.

NHIC-350AT = 3" IC Air-Tight New Construction Housing / 50W max.

NHR-354AT = 3" Non-IC Air-Tight Remodel Housing / 50W max.

Low Voltage

Catalog No.

NLIC-301AT/1EL = 3" IC Air-Tight New Construction Housing / 50W max.

NLIC-301QAT/20 = 3" IC Air-Tight New Construction Housing / 20W max.

NLIC-301QAT/37 = 3" IC Air-Tight New Construction Housing / 37W max.

NLIC-301QAT = 3" IC Air-Tight New Construction Housing / 50W max.

NL-301AT/1EL = 3" Non-IC Air-Tight New Const. Housing / 50W max.

NL-301QAT/20 = 3" Non-IC Air-Tight New Const. Housing / 20W max.

NL-301QAT/37 = 3" Non-IC Air-Tight New Const. Housing / 37W max.

NL-301QAT = 3" Non-IC Air-Tight New Const. Housing / 50W max.

NLR-304AT/1EL = 3" Non-IC Air-Tight Remodel Housing / 50W max.

NLR-304QAT/20 = 3" Non-IC Air-Tight Remodel Housing / 20W max.

NLR-304QAT/37 = 3" Non-IC Air-Tight Remodel Housing / 37W max.

NLR-304QAT = 3" Non-IC Air-Tight Remodel Housing / 50W max.

NLR-305AT/20 = 3" Non-IC Air-Tight Remodel Housing / 20W max.

NLR-305AT/37 = 3" Non-IC Air-Tight Remodel Housing / 37W max.

NLR-305AT = 3" Non-IC Air-Tight Remodel Housing / 50W max.

Example: **NL-3325BZ** = 3" Frosted Dome Lens with Specular Clear Reflector and Bronze Metal Ring