

Type

Project


Catalog No.

Lamp/Wattage

NL-3348

Wall Wash with Baffle

TRIM DIMENSIONS



Trim OD: 3-5/8"
Height: 1-5/8"

FEATURES

Trim

Precision spun 0.040 aluminum baffle with deep grooves to reduce aperture glare with half moon. Non-reflective painted finishes. Gimbal ring allows lamp to be mounted on top of the trim and adjustable up to 35°. Trim ring available in metal, may also be used with custom combination of plastic or metal ring finishes.

Mounting

Trim includes three trim clips that securely mount trim in housing.

Compatible Housings

Compatible with Line Voltage and Low Voltage housings.
See individual specification sheets for more information.

Lamp

Line Voltage

50W 120V MR16 GU10 Max. (NH-350AT; NHIC-350AT; NHR-354AT)

Low Voltage

IMPORTANT: DO NOT USE GLASS LENS (PROVIDED) WHEN ALREADY USING LAMP WITH GLASS COVER
20W-50W 12V MR16 (NL-301 Series; NLIC-301 Series; NLR-304 Series)

Labels and Listings

cULus Listed for Damp Location when used with compatible housing.

Compatible Housings

LINE VOLTAGE

Item Number	Installation Type	Lamp	Dimensions
NH-350AT	Non-IC Air-Tight New Const.	50W MR16	W: 6-3/8" L: 16" H: 5-5/8"
NHIC-350AT	IC Air-Tight New Construction	50W MR16	W: 6-3/8" L: 16" H: 8-1/8"
NHR-354AT	Non-IC Air-Tight Remodel	50W MR16	W: 4-1/4" L: 11-1/4" H: 5-5/8"

LOW VOLTAGE

NL-301QAT/20	Non-IC AT New Const., Mag.	20W MR16	W: 6-3/8" L: 16" H: 5-5/8"
NL-301QAT/37	Non-IC AT New Const., Mag.	37W MR16	W: 6-3/8" L: 16" H: 5-5/8"
NL-301QAT	Non-IC AT New Const., Mag.	50W MR16	W: 6-3/8" L: 16" H: 5-5/8"
NL-301AT/1EL	Non-IC AT New Const., Elec.	50W MR16	W: 6-3/8" L: 16" H: 5-5/8"
NLIC-301QAT/20	IC Air-Tight New Const., Mag.	20W MR16	W: 6-3/8" L: 16" H: 8-1/8"
NLIC-301QAT/37	IC Air-Tight New Const., Mag.	37W MR16	W: 6-3/8" L: 16" H: 8-1/8"
NLIC-301QAT	IC Air-Tight New Const., Mag.	50W MR16	W: 6-3/8" L: 16" H: 8-1/8"
NLIC-301AT/1EL	IC Air-Tight New Const., Elec.	50W MR16	W: 6-3/8" L: 16" H: 8-1/8"
NLR-304QAT/20	Non-IC Air-Tight Remodel, Mag.	20W MR16	W: 4-1/4" L: 11-1/4" H: 5-5/8"
NLR-304QAT/37	Non-IC Air-Tight Remodel, Mag.	37W MR16	W: 4-1/4" L: 11-1/4" H: 5-5/8"
NLR-304QAT	Non-IC Air-Tight Remodel, Mag.	50W MR16	W: 4-1/4" L: 11-1/4" H: 5-5/8"
NLR-304AT/1EL	Non-IC Air-Tight Remodel, Elec.	50W MR16	W: 4-1/4" L: 11-1/4" H: 5-5/8"

Wall Wash with Baffle

NL-3348BB: Black Wall Wash with Black Adjustable Stepped Baffle and Black Metal Ring

NL-3348BW: White Wall Wash with Black Adjustable Stepped Baffle and White Metal Ring

NL-3348WW: White Wall Wash with White Adjustable Stepped Baffle and White Metal Ring