

NL-610 / NL-611

6" Adjustable Stepped Baffle w/ White Plastic Ring

FEATURES

Trim: Precision spun 0.040 aluminum baffle with deep grooves to reduce aperture glare. Non-reflective painted finishes. Gimbal ring allows lamp to be mounted on top of the trim and adjustable up to 35°. Separate plastic ring may be changed to be used with custom combination of ring finishes.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86).

COMPATIBLE LAMP / HOUSINGS

Low Voltage:

20W-50W 12V MR16 (NLIC-601 Series; NL-601 Series; NLR-604 Series)
20W-75W 12V MR16 (NL-601/75 Series; NLR-604/75 Series)

Retrofit Kits:

50W 120V MR16 GU10 Max. (NRA-34/10)

20W-50W 12V MR16 (NLK-2600; NLK-2600/EL)

See individual housing specification sheets for more information.

LABELS AND LISTINGS

cULus Listed for Damp Location when used with compatible housing



Type

Project

Catalog No.


Notes

PRODUCT IMAGES & DIMENSIONS



NL-610

NL-611



6" Adjustable Stepped Baffle w/ White Plastic Ring

Catalog No.

NL-610W = 6" White Adjustable Stepped Baffle with White Plastic Ring

NL-611B = 6" Black Adjustable Stepped Baffle with White Plastic Ring

Compatible Housings

Catalog No.

Low Voltage

NL-601Q = Non-IC New Construction / 120V Magnetic / 20W-50W max

NL-601/1EL = Non-IC New Construction / 120V Electronic / 3W-50W max

NL-601/2EL = Non-IC New Construction / 277V Electronic / 20W-50W max

NL-601/75Q = Non-IC New Construction / 120V Magnetic / 20W-75W max

NL-601/75/1EL = Non-IC New Construction / 120V Electronic / 20W-75W max

NL-601/75/2EL = Non-IC New Construction / 277V Electronic / 20W-75W max

NLIC-601QAT = ICAT New Construction / 120V Magnetic / 20W-50W max

NLIC-601/1EL = ICAT New Construction / 120V Electronic / 3W-50W max

NLIC-601/2EL = ICAT New Construction / 277V Electronic / 20W-50W max

NLR-604Q = Non-IC Remodel / 120V Magnetic / 20W-50W max

NLR-604/1EL = Non-IC Remodel / 120V Electronic / 3W-50W max

NLR-604/2EL = Non-IC Remodel / 277V Electronic / 20W-50W max

NLR-604/75Q = Non-IC Remodel / 120V Magnetic / 20W-75W max

NLR-604/75/1EL = Non-IC New Construction / 120V Electronic / 20W-75W max

NLR-604/75/2EL = Non-IC New Construction / 277V Electronic / 20W-75W max

Low Voltage Retrofit Kits

NLK-2600 = Non-IC / 120V Magnetic

NLK-2600/EL = Non-IC / 120V Electronic

Line Voltage Retrofit Kit

NRA-34/10 = Non-IC / Without Lamp

Example: **NL-610W** = 6" White Adjustable Stepped Baffle with White Plastic Ring