

NOXTW-56 Series

5"/6" Onyx Tunable White Retrofit Reflectors

Source: 15.5W

1100lm

PRODUCT DESCRIPTION

Onyx 5"/6" Tunable White Retrofit Series include an integral tunable CCT switch. Spun aluminum construction provides clean sharp edges and is suitable for use with most 5" and 6" recessed housings. Deep regressed optics and round aperture deliver even and glare-free illumination.

FEATURES

- 1100lm / 15.5W LED light engine
- Selectable CCT (2700K, 3000K, 3500K, 4000K or 5000K @ 90+ CRI)
- Integral dimmable driver
- Includes medium base socket adaptor for easy retrofitting in 5" or 6" recessed housings
- 5-year limited warranty
- ENERGY STAR certified
- cULus classified for wet locations

SPECIFICATION

Reflector: One piece, spun aluminum construction dissipates heat and extends life. Unitized Thermal Management, UTM, provides exceptional cool operation.

Housings: Compatible with most 5" and 6" IC and non-IC housings by Nora and others.

Mounting: Two steel, torsion mounting springs allow for easy and secure mounting in most 5" and 6" housings.

Retrofit: Onyx retrofit series includes medium base screw-socket adapter (NRA-211SM) for retrofitting into existing medium base downlight housings. GU24 socket adapter is available for use with GU24 housings, must specify NRA-212SM.

ELECTRICAL

Input Voltage: 120V

Lumens / Wattage: 1100lm / 15.5W

Color Temperature:

2700K, 3000K, 3500K, 4000K or 5000K (each luminaire includes a CCT switch)

CRI: 90+ CRI

Dimming: Triac or ELV

[Click Here](#) or check complete dimmer list at

www.NoraLighting.com in the "Compatibility" page under "Resources" tab

COMPATIBLE HOUSINGS

Onyx reflectors are compatible with most 5" & 6" IC and Non-IC housings by Nora and others.

Fire Box

NFBIC-5INCATA

NFBIC-5LMRATA*

NFBIC-6INCATA

NFBIC-6LMRATA*

New Construction

NHIC-5LMRAT*

NHIC-5LMRAT/277*¹

NHIC-527LMRAT*

NHIC-501QAT

NHIC-527QAT

NH-501Q

NHIC-5G24ATFL

NHIC-6LMRAT*

NHICCP-6LMRAT*

NHIC-6LMRAT/277*¹

NHIC-27LMRAT*

NHIC-17QAT

NHIC-17QNBAT

NHIC-27QAT

NH-26Q

NH-26QNB

NHIC-6G24ATFL

Remodel

NHRIC-5LMRAT*

NHRIC-527LMRAT*

NHRIC-504QAT

NHRIC-527QAT

NHR-504Q

NHRIC-5G24ATFL

NHRIC-6LMRAT*

NHRIC-27LMRAT*

NHRIC-17QAT

NHRIC-17QNBAT

NHRIC-27QAT

NHR-26Q

NHRIC-6G24ATFL

NHIC-6G24ATFL

* Nora LED Dedicated housings are cULus listed for use only with Nora LED Retrofits.

¹ Housings include a step down transformer

5" ICAT Fire Box

5" ICAT Dedicated LED Fire Box

6" ICAT Fire Box

6" ICAT Dedicated LED Fire Box

5" ICAT Dedicated LED

5" ICAT Dedicated LED, 277V

5" ICAT Shallow Dedicated LED

5" ICAT Line Voltage

5" ICAT Shallow Line Voltage

5" Line Voltage

5" ICAT GU24

6" ICAT Dedicated LED

6" Chicago Plenum Dedicated LED

6" ICAT Dedicated LED, 277V

6" ICAT Shallow Dedicated LED

6" ICAT Line Voltage

6" ICAT Line Volt (No Bracket)

6" ICAT Shallow Line Voltage

6" Line Voltage

6" Line Voltage (No Bracket)

6" ICAT GU24

5" ICAT Dedicated LED

5" ICAT Shallow Dedicated LED

5" ICAT Line Voltage

5" ICAT Shallow Line Voltage

5" Line Voltage

5" ICAT GU24

6" ICAT Dedicated LED

6" ICAT Shallow Dedicated LED

6" ICAT Line Voltage

6" ICAT Line Volt (No Bracket)

6" ICAT Shallow Line Voltage

6" Line Voltage

6" ICAT GU24

LABELS AND LISTINGS

- cULus classified for Wet Locations
- ENERGY STAR certified (WW only)
- [5-Year Limited Warranty](#)
- Meets ASTM-E283 Air-Tight requirements
- FCC compliant
- Certified to the high efficacy requirements of California Title 24 JA8-2019



Type

Project

Catalog No.

Notes

PRODUCT IMAGES AND DIMENSIONS



5"/6" Onyx Tunable White Reflectors

Reflector Type	Color Temperature / CRI	Finish
NOXTW-5631 = Round Reflector	(blank) = 2700K, 3000K, 3500K, 4000K, 5000K	BB = Black / Black Flange (NOXTW-5631 only)
NOXTW-5632 = Round Baffle		WW = White / White Flange

Optional Accessories

Description
NOX-56REFLB = 5'/6" Black Reflector Insert for NOXTW-5631
NOX-56REFLD = 5'/6" Clear Diffused Reflector Insert for NOXTW-5631
NOX-56REFLHZ = 5'/6" Haze Reflector Insert for NOXTW-5631
NOX-56BAFB = 5'/6" Black Baffle Insert for NOXTW-5631
NOX-56BAFW = 5'/6" White Baffle Insert for NOXTW-5631
NOX-56EYELIDW = 5'/6" Round White Eyelid
NOX-56OR-W = 5'/6" Round White Oversize Ring
NOX-56BLADE = 5'/6" Blade for housings without spring brackets
NRA-211SM = Medium base screw-in socket (included w/ each)
NRA-212SM = Socket adapter for use with GU24 housings

Example: NOXTW-5631WW = 5'/6" Onyx Tunable White Round Reflector LED Retrofit, White Reflector / White Flange

NOXTW-56 Series
5"/6" Onyx Tunable White Retrofit Reflector Accessories

Type	
Project	
Catalog No.	
Notes	



Onyx Reflector Insert

NOX-56REFLB Black
NOX-56REFLD Clear Diffused
NOX-56REFLHZ Haze
Round reflector insert is field changeable used to convert the reflector finish for NOXTW-5631.



Onyx Baffle Insert

NOX-56BAFB Black
NOX-56BAFW White
Round baffle insert is field changeable used to convert reflector (NOXTW-5631) to baffle.




Onyx Eyelid

NOX-56EYELIDW White
Round eyelid clips on reflector or baffle to convert into half moon wall wash



Onyx Oversize Ring

NOX-56OR-W White
Round oversize ring covers large ceiling cut-outs up to 8-1/4"



Onyx Blade Replacement

NOX-56BLADE Pair of Two
Replaces torsion springs with mounting blades for recessed housings without spring brackets.



Medium Base Screw-In Socket

NRA-21ISM
Medium base screw-in socket adapter for retrofitting into existing medium base housings. One is included with each luminaire.



Socket Adapter for GU24 Housings

NRA-212SM
GU24 socket adapter for retrofitting into existing GU24 housings.

PHOTOMETRICS

5"/6" Onyx Tunable White Retrofit Reflectors

Type


Project

Catalog No.

Notes

Test Information

Test Number: NTR1173
Part Number: NOXTW-5631WW
Beam Spread: 93° Wide Flood
Lumens: 947lm
Wattage: 15.65W
Efficacy: 60lpw
CCT / CRI: 2700K / 90 CRI
Spacing Criteria (0°-180): 1.18
Spacing Criteria (90°-270): 1.18



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	27.7fc	8'-5"
6'	12.3fc	12'-6"
8'	6.9fc	16'-8"
10'	4.4fc	20'-11"
12'	3.1fc	25'-1"

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	159	16.8
0-40	525	55.4
0-60	835	88.2
0-90	938	99.1
90-180	8	0.9
0-180	947	100

Candela Table

Vertical Angles	Candela
0	443
5	440
15	417
25	372
35	311
45	232

Test Information

Test Number: NTR1174
Part Number: NOXTW-5631WW
Beam Spread: 93° Wide Flood
Lumens: 1057lm
Wattage: 15.45W
Efficacy: 68lpw
CCT / CRI: 3000K / 90 CRI
Spacing Criteria (0°-180): 1.18
Spacing Criteria (90°-270): 1.18



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	30.8fc	8'-5"
6'	13.7fc	12'-7"
8'	7.7fc	16'-10"
10'	4.9fc	21'
12'	3.4fc	25'-4"

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	368	34.8
0-40	585	55.4
0-60	933	88.2
0-90	1049	99.2
90-180	9	0.8
0-180	1057	100

Candela Table

Vertical Angles	Candela
0	493
5	490
15	464
25	415
35	348
45	261

Test Information

Test Number: NTR1175
Part Number: NOXTW-5631WW
Beam Spread: 98° Wide Flood
Lumens: 1087lm
Wattage: 15.43W
Efficacy: 70lpw
CCT / CRI: 3500K / 90 CRI
Spacing Criteria (0°-180): 1.2
Spacing Criteria (90°-270): 1.2



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	29.5fc	9'-2"
6'	13.1fc	13'-10"
8'	7.4fc	18'-5"
10'	4.7fc	23'
12'	3.3fc	27'-7"

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	357	32.8
0-40	573	52.8
0-60	943	86.8
0-90	1078	99.2
90-180	9	0.8
0-180	1087	100

Candela Table

Vertical Angles	Candela
0	471
5	468
15	447
25	405
35	348
45	271

Test Information

Test Number: NTR1176
Part Number: NOXTW-5631WW
Beam Spread: 95° Wide Flood
Lumens: 1134lm
Wattage: 15.36W
Efficacy: 74lpw
CCT / CRI: 4000K / 90 CRI
Spacing Criteria (0°-180): 1.18
Spacing Criteria (90°-270): 1.14



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	31.6fc	8'-10"
6'	14.1fc	13'-2"
8'	7.9fc	17'-7"
10'	5.1fc	21'-11"
12'	3.5fc	26'-4"

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	379	33.4
0-40	606	53.4
0-60	982	86.6
0-90	1121	98.9
90-180	13	1.1
0-180	1134	100

Candela Table

Vertical Angles	Candela
0	506
5	503
15	475
25	424
35	357
45	272

Test Information

Test Number: NTR1177
Part Number: NOXTW-5631WW
Beam Spread: 95° Wide Flood
Lumens: 1118lm
Wattage: 15.36W
Efficacy: 73lpw
CCT / CRI: 5000K / 90 CRI
Spacing Criteria (0°-180): 1.18
Spacing Criteria (90°-270): 1.14



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	31.2fc	8'-10"
6'	13.9fc	13'-2"
8'	7.8fc	17'-7"
10'	5fc	21'-11"
12'	3.5fc	26'-4"

Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	374	33.4
0-40	597	53.4
0-60	969	86.6
0-90	1106	98.9
90-180	12	1.1
0-180	1118	100

Candela Table

Vertical Angles	Candela
0	499
5	496
15	469
25	418
35	352
45	268