

NP-26

6" Frosted Flat Lens with Plastic Trim

Type

Project

Catalog No.

Notes

FEATURES

Trim: High grade frosted flat lens attached to plastic trim.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86).

COMPATIBLE LAMP / HOUSINGS


Line Voltage:
25W A19 Maximum (NHIC-27QAT; NHRIC-27QAT)
40W A19 Maximum (NHIC-17QAT; NHIC-926QAT; NHRIC-17QAT; NHRIC-926QAT)
60W A19 Max. (NH-26Q; NH-27Q; NHIC-17/100DWQA; NHR-26Q; NHR-27Q)
See individual housing specification sheets for more information.

LABELS AND LISTINGS

* cULus Listed for Wet Location when used with compatible housing



PRODUCT IMAGES & DIMENSIONS



6" Frosted Flat Lens with Plastic Trim

Catalog No.

NP-26 = 6" Frosted Flat Lens with White Plastic Trim

Compatible Housings

Catalog No.

NH-26Q = Non-IC New Construction / 60W max
NHR-26Q = Non-IC Remodel / 60W max
NHIC-17/100DWQA = IC Air-Tight Double Wall New Construction / 60W max
NHIC-17QAT = IC Air-Tight New Construction / 40W max
NHRIC-17QAT = IC Air-Tight Remodel / 40W max
NH-27Q = Shallow Non-IC New Construction / 60W max
NHR-27Q = Shallow Non-IC Remodel / 60W max
NHIC-27QAT = Shallow IC Air-Tight New Construction / 25W max
NHRIC-27QAT = Shallow IC Air-Tight Remodel / 25W max
NHIC-926QAT = Sloped IC Air-Tight New Construction / 40W max
NHRIC-926QAT = Sloped IC Air-Tight Remodel / 40W max

Example: NP-26 = 6" Frosted Flat Lens with White Plastic Trim