

NRS12-109

Universal Lamp Holder  
Source: 250W max.

|             |  |
|-------------|--|
| Type        |  |
| Project     |  |
| Catalog No. |  |
| Notes       |  |

PRODUCT DESCRIPTION

Line voltage universal lamp holder with adjustable angle. Smooth, cylindrical design with softened edges on rear of housing for aesthetic, modern appearance. Lateral and vertical swivel enable user to aim the light source to any desired location. Adjustment knob on housing side allows user to extend or retract the neck of the lamp source.

FEATURES

- Deep drawn steel socket cup housing for high strength and rigidity
- Heat resistant Teflon coated wire lead
- Adjustable angle for custom aiming
- High-strength stainless steel electrical contacts

CONSTRUCTION

**Housing:** 0.025" deep drawn steel construction with softened edges for clean, low profile appearance.

**Swivel Arm:** 0.080" rigid steel arm connects fixture housing to electrical contact head. Plastic tightening knob maintains clean, decorative appearance of the fixture.

**Wiring:** Teflon coated wire lead connects socket and housing to electrical contact head. Teflon coating is durable and resists heat degradation from lamp and housing radiation.

**Universal Connector:** 0.07" die-cast aluminum shell with copper positive and neutral contacts.

ELECTRICAL


**Input Voltage:** 120V  
**Socket:** Medium Base  
**Lamp Type:** PAR20, PAR30 or PAR38  
**Wattage:** 250W max.

LABELS AND LISTINGS

cULus Listed for Dry Location



PRODUCT IMAGES AND DIMENSIONS



Universal Lamp Holder

| Series                            | Finish                                                           |
|-----------------------------------|------------------------------------------------------------------|
| NRS12-109 = Universal Lamp Holder | BN = Brushed Nickel<br>BZB = Black Fixture with Bronze Connector |

Example: NRS12-109BN = Universal Lamp Holder, Brushed Nickel finish