

NTE-842

Aiden LED Track Head

Source: 35W LED
2200lm

Type

Project

Catalog No.

Notes

PRODUCT DESCRIPTION

Aiden is a high-lumen LED track head available in two different beam spreads and can be adjusted 350° horizontally and 90° vertically. Designed for use in retail, commercial and residential environments, heat-dissipating fins optimize heat management. Aiden is offered in two color temperatures, 3000K warm white and 4000K cool white @ 80 or 90 CRI. Aiden has one or two circuit track capability and comes in standard H-style or optional J- or L-style. Finishes include black, white and silver.

FEATURES

- Over 75% energy savings when compared to incandescent
- 2200lm LED output
- 3000K or 4000K @ 80 or 90 CRI
- Integral dimmable driver
- 18° Spot or 38° Flood beam spread
- 5-Year Limited Warranty

CONSTRUCTION

Die-cast aluminum head and body for maximum heat dissipation, with integral driver.

Adjustability: 350° horizontal and 90° vertical rotation

ELECTRICAL

Voltage: 120 VAC, 50/60 Hz

Lumens / Wattage: 2200lm / 35W (80 CRI) or 30W (90 CRI)

CRI: 80 or 90

Beam Spread: 18° Spot or 38° Flood

Color Temperature: 3000K or 4000K

Dimming: Triac or ELV

[Click Here](#) or check complete dimmer list at www.NoraLighting.com in the "Compatibility" page under "Resources" tab

FINISH

Available in black, silver and white finishes.

ONE / TWO CIRCUIT CONVERSION


Positive contact (opposite neutral and ground contacts) is preset to "down" position at factory, but may be raised to the higher position to install onto the second circuit of Nora Lighting NT-2300 series two-circuit track.

LABELS AND LISTINGS

- cULus Listed
- [5-Year Limited Warranty](#)



PRODUCT IMAGES & DIMENSIONS



Aiden LED Track Head

Series	Color Temperature / CRI	Beam Spread	Lumens / Wattage	Finish
NTE-842L	30 = 3000K / 80 CRI	S = 18° Spot	35 = 2200lm / 35W	B = Black
	40 = 4000K / 80 CRI	F = 38° Flood		S = Silver
				W = White
NTE-842L	930 = 3000K / 90 CRI	S = 18° Spot	30 = 2200lm / 30W	B = Black
	940 = 4000K / 90 CRI	F = 38° Flood		S = Silver
				W = White

Optional Accessories

Description

NT-339CPB = Barn Door, Black

NT-339CPS = Barn Door, Silver

NT-339CPW = Barn Door, White



Example: **NTE-842L30F35B** = 2200lm / 35W Aiden LED Track Head, 3000K / 80 CRI, 38° Flood, Black Finish

PHOTOMETRICS

Aiden LED Track Head

Type


Project

Catalog No.

Notes

Test Information

Test Number: 284648
Part Number: NTE-842L30S35
Beam Spread: 18° Spot
Lumens: 2264lm
Wattage: 35.5W
Efficacy: 64lpw
CCT / CRI: 3000K / 80 CRI
Spacing Criteria (0°-180): 0.32
Spacing Criteria (90°-270): 0.32



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
6'	360fc	1'-11"
9'	160fc	2'-11"
12'	89.9fc	3'-10"
15'	57.5fc	4'-10"
18'	40fc	5'-8"

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	2171	95.9
0-40	2243	99.1
0-60	2262	99.9
0-90	2264	100
90-180	0	0
0-180	2264	100

Candela Table

Vertical Angles	Candela
0	12944
5	10726
15	3043
25	973
35	81
45	19

Test Information

Test Number: 284650
Part Number: NTE-842L30F35
Beam Spread: 38° Flood
Lumens: 2185lm
Wattage: 34.6W
Efficacy: 63lpw
CCT / CRI: 3000K / 80 CRI
Spacing Criteria (0°-180): 0.64
Spacing Criteria (90°-270): 0.64



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
6'	149fc	4'-1"
9'	66.1fc	6'-2"
12'	37.2fc	8'-2"
15'	23.8fc	10'-4"
18'	16.5fc	12'-5"

Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	2068	94.7
0-40	2156	98.7
0-60	2183	99.9
0-90	2185	100
90-180	0	0
0-180	2185	100

Candela Table

Vertical Angles	Candela
0	5357
5	5171
15	3692
25	1298
35	94
45	25