

# NT-5000

## 5" Metal Splay Trim with Bracket

Type

Project

Catalog No.

Notes

### FEATURES

**Trim:** Metal splay trim with 4-5/8" open center.

**Mounting:** Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86).

### COMPATIBLE HOUSINGS

Compatible with Line Voltage housings. See individual specification sheets for more information.

### LAMP

Line Voltage

75W BR30/PAR30 (NH-501Q; NHIC-501QAT; NHR-504Q; NHRIC-504QAT; NFBIC-5INCATA)

GU24

13W-26W GU24 (NHIC-5G24ATFL)

### LABELS AND LISTINGS

· cULus Listed for Damp Location when used with compatible housing



### PRODUCT IMAGES AND DIMENSIONS



NT-5000BZ




NT-5000CO



NT-5000N



NT-5000W



## 5" Metal Splay Trim with Bracket

Catalog No.

**NT-5000BZ** = Bronze Metal Splay Trim with Bracket

**NT-5000CO** = Copper Metal Splay Trim with Bracket

**NT-5000N** = Natural Metal Metal Splay Trim with Bracket

**NT-5000W** = White Metal Metal Splay Trim with Bracket

## Compatible Housings

### Line Voltage

Catalog No.

**NHIC-501QAT** = 5" IC Air-Tight New Construction / 75W max

**NHRIC-504QAT** = 5" IC Air-Tight Remodel / 75W max

**NH-501Q** = 5" Non-IC New Construction / 75W max

**NHR-504Q** = 5" Non-IC Remodel / 75W max

**NFBIC-5INCATA** = 5" IC Air-Tight Fire Rated New Construction / 75W max

### GU24

Catalog No.

**NHIC-5G24ATFL** = 5" IC Air-Tight GU24 New Construction / 13W-26W max

Example: **NT-5000BZ** = Bronze Metal Splay Trim with Bracket