

NT-5010

5" Stepped Baffle with Metal Ring and Bracket

FEATURES

Trim: Precision spun 0.040 aluminum baffle insert with deep grooves to reduce aperture glare. Non-reflective painted finishes. Trim may also be used with custom combination of ring finishes. Bracket includes two socket positions for optimum light control and output.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86).

COMPATIBLE HOUSINGS

Compatible with Line Voltage housings. See individual specification sheets for more information.

LAMP

50W BR30/PAR30 Maximum (NHIC-501QAT; NHRIC-504QAT)

75W BR30/PAR30 Maximum (NH-501Q; NHR-504Q; NFBIC-5INCATA)

LABELS AND LISTINGS

· cULus Listed for Damp Location when used with compatible housing



Type

Project

Catalog No.

Notes

PRODUCT IMAGES AND DIMENSIONS




NT-5010B



NT-5010N



NT-5010W



5" Stepped Baffle with Metal Ring and Bracket

Catalog No.

NT-5010B = Black Stepped Baffle with White Metal Ring and Bracket

NT-5010N = Natural Metal Stepped Baffle with Natural Metal Ring and Bracket

NT-5010W = White Stepped Baffle with White Metal Ring and Bracket

Compatible Housings

Catalog No.

NH-501Q = 5" Non-IC New Construction / 75W max

NHR-504Q = 5" Non-IC Remodel / 75W max

NHIC-501QAT = 5" IC Air-Tight New Construction / 50W max

NHRIC-504QAT = 5" IC Air-Tight Remodel / 50W max

NFBIC-5INCATA = 5" IC Air-Tight New Construction / 50W max

Example: **NT-5010B** = Black Stepped Baffle with White Metal Ring and Bracket