

NT-5021

5" Reflector Cone with Metal Ring

Type

Project

Catalog No.

Notes

FEATURES

Trim: Precision spun 0.050 high grade aluminum reflector and metal trim ring may also be used with custom combination of ring finishes.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86). Remove socket from socket plate within housing (if applicable), and mount socket onto bracket.

COMPATIBLE HOUSINGS

Compatible with Line Voltage and GU24 housings. See individual specification sheets for more information.

LAMP

Line Voltage

60W A19 (NH-501Q; NHR-504Q; NFBIC-5INCATA)

40W A19 (NHIC-501QAT; NHRIC-504QAT)

GU24

13W-26W GU24 (NHIC-5G24ATFL)

LABELS AND LISTINGS

· cULus Listed for Damp Location when used with compatible housing



PRODUCT IMAGES AND DIMENSIONS




NT-5021B



NT-5021W



NT-5021C



5" Specular Reflector with White Metal Ring

Catalog No.

NT-5021B = Specular Black Reflector with White Metal Ring

NT-5021C = Specular Clear Reflector with White Metal Ring

NT-5021CO = Copper Reflector with Copper Metal Ring

NT-5021G = Specular Black Reflector with White Metal Ring

NT-5021HZ = Haze Reflector with White Metal Ring

NT-5021N = Natural Metal Reflector with Natural Metal Metal Ring

NT-5021W = Specular White Reflector with White Metal Ring

Compatible Housings

Catalog No.

NHIC-501QAT = 5" IC Air-Tight New Construction / 40W max

NHRIC-504QAT = 5" IC Air-Tight Remodel / 40W max

NH-501Q = 5" Non-IC New Construction / 60W max

NHR-504Q = 5" Non-IC Remodel / 60W max

NFBIC-5INCATA = 5" IC Air-Tight Fire Rated New Construction / 60W max

GU24

Catalog No.

NHIC-5G24ATFL = 5" IC Air-Tight GU24 New Construction / 13W-26W max

Example: **NT-5021W** = Specular White Reflector with White Metal Ring