

NT-5050

5" Front Loading Frosted Dome Lens with Reflector and Trim

Type

Project

Catalog No.

Notes

FEATURES

Trim: Precision spun 0.050 aluminum high grade reflector with high grade frosted dome lens attached to trim. Easy lift and turn lens removal for re-lamping. Reflector includes two socket positions for optimum light control and output.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86). Remove socket from socket plate within housing (if applicable), and mount directly onto trim.

COMPATIBLE HOUSINGS

Compatible with Line Voltage housings. See individual specification sheets for more information.

LAMP

35W PAR30 (NHIC-527QAT; NHRIC-527QAT)

40W A19 (NHIC-501QAT; NHRIC-504QAT)

60W A19 (NH-501Q; NHR-504Q)

LABELS AND LISTINGS

· cULus Listed for Wet Location when used with compatible housing



PRODUCT IMAGES AND DIMENSIONS



5" Front Loading Frosted Dome Lens with Reflector and Trim

Catalog No.

NT-5050W = Front Loading Frosted Dome Lens with Specular Clear Reflector and White Plastic Trim

Compatible Housings

Catalog No.

NH-501Q = 5" Non-IC New Construction Housing / 60W max

NHR-504Q = 5" Non-IC Remodel Housing / 60W max

NHIC-501QAT = 5" IC Air-Tight New Construction Housing / 40W max

NHRIC-504QAT = 5" IC Air-Tight Remodel Housing / 40W max

NHIC-527QAT = 5" Shallow IC Air-Tight New Construction Housing / 35W max

NHRIC-527QAT = 5" Shallow IC Air-Tight Remodel Housing / 35W max

Example: **NT-5050W** = Front Loading Frosted Dome Lens with Specular Clear Reflector and White Plastic Trim