

NT-5061

5" Stepped Baffle with Adjustable Gimbal

Type

Project

Catalog No.

Notes

FEATURES

Trim: Precision spun 0.040 baffle with deep grooves to reduce aperture glare. Trim with gimbal ring can be adjusted up to 30°.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86). Remove socket from socket plate within housing (if applicable), and mount directly onto trim.

COMPATIBLE HOUSINGS

Compatible with Line Voltage housings. See individual specification sheets for more information.

LAMP

75W PAR30 Maximum (NH-501Q; NHIC-501QAT; NHR-504Q; NHRIC-504QAT)

LABELS AND LISTINGS

· cULus Listed for Damp Location when used with compatible housing



PRODUCT IMAGES AND DIMENSIONS




NT-5061CO



NT-5061N



NT-5061W



4-5/8"
6-1/2"

5" PAR30 Stepped Baffle with Adjustable Gimbal

Catalog No.

NT-5061BZ = Bronze Stepped Baffle with Bronze Adjustable Gimbal and Bronze Flange
NT-5061CO = Copper Stepped Baffle with Copper Adjustable Gimbal and Copper Flange
NT-5061N = Natural Metal Stepped Baffle with Natural Metal Adjustable Gimbal and Natural Metal Flange
NT-5061W = White Stepped Baffle with White Adjustable Gimbal and White Flange

Compatible Housings

Catalog No.

NH-501Q = 5" Non-IC New Construction Housing / 75W max
NHR-504Q = 5" Non-IC Remodel Housing / 75W max
NHIC-501QAT = 5" IC Air-Tight New Construction Housing / 75W max
NHRIC-504QAT = 5" IC Air-Tight Remodel Housing / 75W max

Example: **NT-5061B** = Black Stepped Baffle with Black Adjustable Gimbal and Black Flange