

NT-5070
5" BR/PAR30 Eyeball with Metal Trim

Type

Project

Catalog No.

Notes

FEATURES
Trim: Adjustable metal trim can be rotated 358° horizontally and 30° vertically. Eyeball includes two socket positions for optimum light control and output.
Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86). Remove socket from socket plate within housing (if applicable), and mount directly onto trim.

COMPATIBLE HOUSINGS
Compatible with Line Voltage housings. See individual specification sheets for more information.

LAMP
50W PAR30 Maximum (NHIC-527QAT; NHRIC-527QAT)
75W BR30/PAR30 Maximum (NH-501Q; NHIC-501QAT; NHR-504Q; NHRIC-504QAT; NFBIC-5INCATA)


LABELS AND LISTINGS
· cULus Listed for Damp Location when used with compatible housing



PRODUCT IMAGES AND DIMENSIONS



NT-5070CO NT-5070W



5" BR/PAR30 Eyeball with Metal Trim

Catalog No.

NT-5070CO = Copper BR/PAR30 Eyeball with Copper Metal Trim
NT-5070W = White BR/PAR30 Eyeball with White Metal Trim

Compatible Housings

Catalog No.

NH-501Q = 5" Non-IC New Construction Housing / 75W max
NHR-504Q = 5" Non-IC Remodel Housing / 75W max
NHIC-501QAT = 5" IC Air-Tight New Construction Housing / 75W max
NHRIC-504QAT = 5" IC Air-Tight Remodel Housing / 75W max
NHIC-527QAT = 5" Shallow IC Air-Tight New Construction Housing / 50W max
NHRIC-527QAT = 5" Shallow IC Air-Tight Remodel Housing / 50W max
NFBIC-5INCATA = 5" Line Voltage IC Air-Tight Fire Rated Housing / 75W max

Example: NT-5070W = White BR/PAR30 Eyeball with White Metal Trim